logo not found or type unknown

Firma: Player Plus doo Adresa: Svetogorska 9 Telefon: +381 11 3347 442 Fax: +381 11 3347 615

DID: 100000344

PIB: 106966344

E-mail: porudzbine@player.rs

Bowerst & Wilkins HTM6 S2 Anniversary White Central

Bowers & Wilkins HTM6 S2 Anniversary White Centralni zvučnik

Šifra: 17191

Kategorija prozivoda: Centralni Zvučnici

Proizvođač: Bowers & Wilkins

Cena: 50.280,00 rsd

Celebrate clarity

Powerful enough to partner with 603s and compact enough to fit with any piece of furniture, HTM6 S2 Anniversary Edition brings more realism and accuracy to your movie experience.

Layered, beautiful details

The new HTM6 S2 Anniversary Edition adopts a refined and upgraded version of the proven Decoupled Double Dome tweeter, offering 38kHz breakup performance. The result? An accurate and immersive reproduction of your favourite music.

Truly amazing sound

Voices and instruments are delivered with purity and precision, thanks to the revolutionary Continuum™ cone, as found in our flagship 800 Series Diamond. Once reserved for only our most revered models, Continuum brings you a cleaner and more accurate performance.

Upgraded and optimised crossovers

As well as celebratory cosmetic changes, 600 Series Anniversary also benefits from a new optimised crossover design featuring carefully selected components, offering greater insight from your music.

600 Series Anniversary Edition

The essential loudspeakers for music lovers.

Size & weight

| Dimensions | Height: 160mm (6.3 in) Width: 480mm (18.9 in) Depth: 255mm (10 in) cabinet 279mm (11 in) including grille |
|------------|--|
| Net weight | 7.8kg (17.2 lb) |

Technical details

| Technical features | Decoupled Double Dome alum Continuum™ cone FST™ midro Flowport™ |
|-----------------------------|---|
| Description | 2-way vented-box system |
| Drive units | 1x ø25mm (1 in) Aluminum do 2x ø130mm (5 in) Continuum |
| Frequency range | -6dB at 42Hz and 33kHz |
| Frequency response | 72Hz - 28kHz ±3dB |
| Sensitivity | 87dB spl (2.83Vrms, 1m) |
| Harmonic distortion | 2nd and 3rd harmonics (90dB <1% 100Hz - 22kHz <0.5% 200Hz - 22kHz |
| Nominal impedance | 8Ω (minimum 4.3Ω) |
| Recommended amplifier power | 30W - 120W into 8Ω on unclip |