

Bowers & Wilkins 705 S3 Mocha zvučnik za policu/stalak

Šifra: 17454

Kategorija proizvoda: Bookshelf Zvučnici

Proizvođač: Bowers & Wilkins

Cena: 149.880,00 rsd



Experience the detail

This uncompromising two-way speaker reveals subtle nuances in music others miss. Its high-performance features include a solid body Tweeter-on-Top design borrowed from the 800 Series Diamond.

A house for high frequencies

The 700 Series features the latest generation of our iconic Solid Body Tweeter-on-Top housing. Its new, more elongated form incorporates a longer tube-loading system to produce an even more free and open sound with high frequencies. The carefully decoupled housing is milled from a single solid block of aluminum to better resist resonance.

Sharper detail

Carbon Dome tweeters are purpose-built for the 700 Series. Delivering a dramatic improvement on the aluminum double dome tweeter, they raise the breakup threshold to 47kHz, for pinpoint imaging accuracy and detail.

Truly amazing sound

Thanks to its composite construction, the Continuum™ cone avoids the abrupt transitions in behavior that can impair the performance of a conventional drive unit. The result is a more open, neutral performance that delivers voices and instruments with precision and transparency.

Size & weight

Dimensions

Height

345mm (13.6 in) cabinet only

413mm (16.3 in) including tweeter

Width

192mm (7.6 in) cabinet only

Depth

297mm (11.7 in) cabinet only

337mm (13.3 in) including grille and terminals

Net weight

9.58kg (21.1 lb)

Technical details**Technical features**

Decoupled Carbon Dome tweeter

Solid Body Tweeter-on-Top

Continuum™ cone bass / midrange

Flowport™

Max recommended cable

impedance

0.1Ω

Description**2-way vented-box system****Drive units**

1x ø25mm (1 in) Decoupled Carbon Dome high-frequency

1x ø165mm (6.5 in) Continuum cone bass / midrange

Frequency range

45Hz and 33kHz

Frequency response

50Hz - 28kHz ±3dB

Sensitivity	88dB spl (2.83Vrms, 1m)
Harmonic distortion	2nd and 3rd harmonics (90dB, 1m on axis)
	<1% 100Hz - 22kHz
	<0.5% 150Hz - 20kHz
Nominal impedance	8Ω (minimum 3.7Ω)
Recommended amplifier power	
	30W - 120W into 8Ω on unclipped programme