

ORTOFON 2M Red Gramofonska Glava

Šifra: 17572

Kategorija proizvoda: Igle i Glave

Proizvođač: Ortofon

Cena: 11.880,00 rsd



Features:

The 2M Red features a tipped Elliptical diamond and split pole pins with a copper wire.

The engine provides an increased output of 5.5 mV and an optimized sound reproduction and a high level of sonic accuracy.

Designed for easy mounting of the cartridge, and for the weight and size to fit the most common turntables on the market today. The 2M Series provides excellent compatibility when used in an assortment of playback systems and with a wide variety of phono preamps.

2M Red delivers an open, dynamic sound with a slight touch of warmth.

2M Red Technical data

Output voltage at 1000 Hz, 5cm/sec	5.5 mV
Channel balance at 1 kHz	1,5 dB
Channel separation at 1 kHz	22 dB
Channel separation at 15 kHz	15 dB
Frequency range at - 3dB	20-22.000 Hz
Frequency response	20-20.000 Hz + 2 / - 1 dB
Compliance, dynamic, lateral	20 μ m/mN

Stylus type	Elliptical
Stylus tip radius	r/R 8/18 μm
Tracking force range	1,6-2,0g (16-20 mN)
Tracking force, recommended	1,8 g (18 mN)
Tracking angle	20°
Internal impedance, DC resistance	1,3 kOhm
Internal inductance	700 mH
Recommended load resistance	47 kOhm
Recommended load capacitance	150-300 pF
Cartridge weight	7.2 g

Replacement stylus unit - 2M Red (interchangeable with 2M Blue and 2M Silver)

Stylus lifetime: with proper care we find that up to 1000 hours is possible without degradation of performance. Please read about stylus care on our FAQ.

2M Series styli interchangeability:

The 2M Series' engines, coils and magnets configurations are not identical: Red and Blue are identical, so are the Bronze and Black and so are the true mono variants 2M Mono and 2M 78. Likewise, 2M series styli are interchangeable within the below combinations:

- 2M Red, 2M Blue and 2M Silver
- 2M Bronze, 2M Black and 2M Black LVB 250
- 2M Mono and 2M 78

Compatibility with Rega brand TT/TA:

REGA brand cartridges' height from stylus tip to the top cartridge mounting surface is lower than standard. Therefore you would need spacers to ensure the correct set-up of the Ortofon cartridge. Please read about cartridge set-up and alignment on tonearm on our FAQ.

Adjusting the height of your Rega tonearm is easy with Acoustic Signature's Spacer Set. It allows you to adjust the height from 0.5 mm to 3.5 mm in precise steps of 0.5 mm - without removing the tone arm. Simply loosen the screws, insert the AS-spacer, then lock the screws back down, and you're tonearm is ready to play.

3.2 - 4 mm spacers should be enough for 2M cartridge.