

Firma: Player Plus doo Adresa: Svetogorska 9 Telefon: +381 11 3347 442 Fax: +381 11 3347 615

PIB: 106966344

E-mail: porudzbine@player.rs

# Bowers & Wilkins 603 S3 White Podnostojeći Zvučnik

Šifra: 17841

Kategorija prozivoda: Podnostojeći Zvučnici

Proizvođač: Bowers & Wilkins

Cena: 95.880,00 rsd



## Layered, beautiful details

The new 603 S3 introduces our all-new Titanium Dome tweeter, which combines exceptional resolution and insight with smooth, refined high-frequency reproduction. The result? An accurate and immersive insight into your favourite music.

### Truly amazing sound

603 S3 introduces our new and even more acoustically transparent tweeter grille mesh, first developed for our revered Signature models. Alongside the new Titanium Dome tweeter, the resolution and realism is exceptional.

#### **Precision and transparency**

Thanks to its composite construction, the Continuum cone avoids the abrupt transitions in behavior that can impair the performance of a conventional drive unit. With 603 S3, experience a more open, neutral performance that delivers voices and instruments with precision and transparency.

## **Upgraded speaker terminals**

Derived from the speaker terminals recently introduced in our 700 Series range, the speaker terminals on the new 603 S3 feature an improved layout and a cleaner signal path between your amplifier and your loudspeakers.

#### 600 Series

The essential loudspeakers for music lovers.

## Size & weight

| Dimensions                                      | Height: 985 m<br>1,020 mm (40<br>Width: 190 mi<br>260 mm (10.2<br>Depth: 340 m<br>368 mm (14.5<br>402 mm (15.8 |
|---|--|
| Net weight                                      | 27.5kg (60.6 l   |
| Technical details                               |  |
| Technical features                              | Decoupled Do<br>Continuum™ (<br>Paper bass co<br>Flowport™   |
| Description                                     | 3-way vented   |
| Drive units                                     | 1x ø25mm (1<br>1x ø150mm (6<br>2x ø165mm (6  |
| Frequency range                                 | -6dB 29Hz - 3:   |
| Frequency response (+/-3dB from reference axis) | 46Hz - 28kHz   |
| Sensitivity (on axis at 2.83Vrms at 1m)         | 90dB   |
| Harmonic distortion                             | 2nd and 3rd h<br><1% 100Hz -<br><0.5% 350Hz  |

| Nominal impedance               | 8Ω (minimum           |
|---------------------------------|-----------------------|
| Recommended amplifier power     | 30W - 200W ii         |
| Max recommended cable impedance | 0.1Ω                  |
| Finishes                        |                       |
| Cabinet finishes                | Black<br>White<br>Oak |
| Grille finishes                 | Grey (White a         |
|                                 |                       |
|                                 |                       |
|                                 |                       |
|                                 |                       |
|                                 |                       |