OGOe not found or type unknown

Firma: Player Plus doo Adresa: Svetogorska 9 Telefon: +381 11 3347 442 Fax: +381 11 3347 615

PIB: 106966344

E-mail: porudzbine@player.rs

Bowers & Wilkins HTM6 S3 Black Centralni zvučnik

Šifra: 17848

Kategorija prozivoda: Centralni Zvučnici

Proizvođač: Bowers & Wilkins

Cena: 77.880,00 rsd

Bowerst & Wilkins HTM6 & Black Centralni zvučnik

Celebrate clarity

Powerful enough to partner with 603 S3 and compact enough to fit with any piece of furniture, HTM6 S3 brings more realism and accuracy to your home theater experience.

Layered, beautiful details

The new HTM6 S3 introduces our all-new Titanium Dome tweeter, which combines exceptional resolution and insight with smooth, refined high-

7.7kg (17lb)

frequency reproduction. The result? An accurate and immersive insight into your favourite music.

Truly amazing sound

HTM6 S3 introduces our new and even more acoustically transparent tweeter grille mesh, first developed for our revered Signature models. Alongside the new Titanium Dome tweeter, the resolution and realism is exceptional.

Precision and transparency

Thanks to its composite construction, the Continuum cone avoids the abrupt transitions in behavior that can impair the performance of a conventional drive unit. With HTM6 S3, experience a more open, neutral performance that delivers voices and instruments with precision and transparency.

Upgraded speaker terminals

Derived from the speaker terminals recently introduced in our 700 Series range, the speaker terminals on the new HTM6 S3 feature an improved layout and a cleaner signal path between your amplifier and your loudspeakers.

600 Series

The essential loudspeakers for music lovers.

Size & weight

Net weight

Dimensions

Height: 160 m
Width: 480 m
Depth: 255 m
283 mm (11.2

Technical details

Technical features	Decoupled Do Continuum™ o Flowport™
Description	2-way vented-
Drive units	1x ø25mm (1 2x ø130mm (9
Frequency range	-6dB 42Hz - 3:
Frequency response	72Hz - 28kHz
Sensitivity	87dB spl (on a
Harmonic distortion	2nd and 3rd h <1% 100Hz - <0.5% 120Hz
Nominal impedance	8Ω (minimum
Recommended amplifier power	30W - 120W ii
Max recommended cable impedance	0.1Ω

Finishes

Cabinet finishes	Black
Grille finishes	Black (Black)