

## ARCAM Radia A15 Integrirano Pojačalo

Šifra: 17966

Kategorija proizvoda: Integrirana Pojačala

Proizvođač: ARCAM

**Cena: 143.880,00 rsd**



The  
"A" in

ARCAM stands for Amplification - this is our core competence. The A15 is the latest in more than 45 years of amplifier design and manufacture. New components and materials have been painstakingly analysed and reviewed to ensure brilliant sound performance.

So you can play music straight out of the box, the ARCAM A15 includes a Bluetooth solution with Qualcomm AptX Adaptive technology. This provides up to 24-bit HD audio for the best sound quality from your phone or tablet, no matter what you are playing. It can also connect to Bluetooth headphones so your listening experience can continue sensitively after dark.

Hi-res audio is included with high resolution digital audio inputs included.

Like any ARCAM integrated amplifier, we pay particular attention to the built in phono stage to ensure your records sound as lush and engaging as possible.

ARCAM Class AB amplification - provides brilliant musicality

80W per channel 8Ω - powers loudspeakers with dynamics.

Bluetooth with aptX™ Adaptive Technology - for the best sound with the most convenience

Specially selected components and materials - to deliver on sound quality

Wired or Wireless Headphones - connect your headphones for quiet listening with, or without wires

All new Radia design - Purposeful yet playful

MM phono stage - ready for Turntables

Hi-Res Digital Audio Inputs

Plastic Free Packaging - for easy disposal of natural materials

Specification	
<b>Continuous power output (0.5% THD), per channel</b>	80W (8Ω), 120W (4Ω)
<b>Harmonic distortion, 80% power, 8Ω at 1kHz</b>	0.002%

<b>Number of analog inputs</b>	3 (RCA pairs)
<b>Signal-to-noise ratio (A-wtd, ref. 50W, 1V input)</b>	106dB
<b>Frequency response</b>	20Hz—20kHz $\pm$ 0.2dB
<b>Phono (MM) Input impedance</b>	47k $\Omega$ + 100pF
<b>Phono (MM) Input frequency response (ref. RIAA curve)</b>	20Hz—20kHz $\pm$ 1dB
<b>Phono (MM) Input signal-to-noise ratio (A-wtd, ref. 50W, 0dBFS)</b>	109dB
<b>Coaxial (RCA) supported sample rates (kHz)</b>	192, 176.4, 96, 88.2, 48, 44.1
<b>Optical (Toslink) supported sample rates (kHz)</b>	192, 176.4, 96, 88.2, 48, 44.1
<b>Supported bit depths (bit)</b>	24, 16
<b>Frequency response (filter 1)</b>	20Hz—20kHz $\pm$ 0.2dB
<b>Headphone output maximum output level (RMS) into 32<math>\Omega</math>/300<math>\Omega</math></b>	2.5V/5Vrms
<b>Headphone load range</b>	16 $\Omega$ - 2k $\Omega$
<b>Mains voltage</b>	100V or 110-120V or 220-240V, 50-60Hz
<b>Power consumption (maximum)</b>	500W
<b>Power consumption (standby)</b>	<0.5W
<b>Dimensions W x D (including speaker terminals) x H (including feet)</b>	431 x 344 x 98mm
<b>Weight (net)</b>	10kg
<b>Weight (packed)</b>	13kg
<b>Supplied accessories</b>	Mains lead(s), Remote control with 2 x AAA batteries, Quick Start Guide, Important Safety Instructions