

## 2x Technics SL-1210 MK7 + MWM Phase Essential - Dva Gramofona+DVS Kontroler DJPaket

2x Technics SL-1210 MK7 + MWM Phase Essential - Dva

Šifra:  
Kategorija proizvoda: DJ Paketi  
Proizvođač: Technics

Cena: **269.880,00** rsd

### Direct Drive Turntable System SL-1210MK7

Technics SL-1210 MK7 je sledeća serija legendarne serije SL-1210 i odlikuje se tradicionalnim dizajnom gramofona Technics SL-1210 tako da svako ko je ikada koristio ili video prethodni model u novom će prepoznati SL-1210 gramofon. Ovo je prvi novi DJ gramofon koji je Technics proizveo tokom 9 godina i dolazi sa novim funkcijama kao što su motor sa direktnim pogonom bez jezgra i najnovijom tehnologijom upravljanja motorom.

#### Specifikacije:

Tehnologija za rotacionu stabilnost  
Bezjezgtreni motor na direktni pogon  
Vrlo precizni motor kontroler  
Konstrukcija za toleranciju vibracija  
Tanjir koji prigušuje vibracije  
Čvrsta konstrukcija  
Inzulator za ublažavanje vibracija  
Visoko kvalitetni delovi  
Visoko osetljiva tonska ručica  
Odvojivi PHONO terminal  
Technics dizajn  
Na osnovu serije SL-1200  
Gramofonska sekcija  
Pogon: direktni  
Brzine gramofona: 33 1/3, 45rpm (sa prekidačem 78 rpm)  
Startni okretni moment: 0.18 N.m / 1.8kg.cm (1.56 lbs-in)  
Build-up karakteristike: 0.7 s. od mirovanja do 33 1/3 rpm  
Wow i Flutter: 0.025% W.R.M.S.  
Gramofonski tanjir: Liveni aluminijum  
Prečnik: 332mm (13-5/64")  
Težina: približno 1.8kg (4.0 lbs) (uključujući slipmat i slipsheet)  
Tonska ručica  
Tip: univerzalna, statički balansirana  
Efektivna dužina: 230mm (9-1/16")  
Overhang: 15mm (19/32")  
Gazna greška:  
U okviru 2 stepena 32' (na spoljnom urezu od 30cm (12") ploče)  
U okviru 0 stepena 32' (na unutrašnjem urezu od 30cm (12") ploče)  
Offset ugao: 22 stepeni / opseg podešavanja visine ručice: 0 - 6mm  
Opseg podešavanja pritiska igle: 0 - 4g (direktno čitanje)

Težina nosača glave: približno. 7.6g

Opseg primenjive težine glave: [bez dodatne težine] 5.6 12.0g (14.3 20.7g (uključujući glavu))

Terminal Lug glave: 1.2mmf 4-pin terminal lug

Terminali

Audio izlaz: PHONO (Pin DŽEK) x 1, Earth Terminal x 1

Opšte

Potrošnja struje: 8W (približno 0.2W (Standby))

Dimenzije (Š x V x D): 453 x 169 x 353mm (17-27/32 x 6-21/32 x 13-29/32 inča)

Težina: približno 9.6kg (21.2lbs)

Dodatna oprema: Gramofon, Slipmat, Slipsheet, Poklopac za prašinu, adapter za EP ploče, težina za balans, nosač glave, set za monitiranje glave, PHONO kabl, PHONO uzemljenje, AC kabl za napajanje, Priručnik za korišćenje

## **Phase Essential - DVS kontroler**

Perfectly accurate

The same level of stability as digital DJ controllers

No more rumble or common DJ equipment issues

Ready to use with any DVS setup

10-hour battery-life per Remote

2 stereo RCA outputs

USB connection to power and configure Phase

2.4 GHz signal radio frequency

32 bits / 96kHz audio support

Robust and impact resistant

What's in the box?

1 Phase Receiver

2 Phase Remotes

2 MWM RCA Cables

1 MWM USB Cable

4 Phase Magnetic Stickers

1 Quick Start Guide

Full specs

Dimensions

Receiver: 4.8x2.8x1 (inches)

Remote: 2.6x0.9x0.3 (inches)

Finishing

Aluminium, robust and resistant

Remote: magnetised surface to maintain the Remote

Buttons and connection

Receiver: setup buttons A and B to setup the Remotes

2.4 GHz signal radio frequency

USB port to turn on the Receiver and charge the Remotes

Power and battery

10-hour battery-life per Remote

Built-in rechargeable Lithium-ion

Charging via USB computer port or power adapter

2-hour charging

Compatibility

Connects to all DVS setup via its 2 RCA outputs

Compatible with the following DJ software Serato DJ, Virtual DJ, Rekordbox, Traktor

Environmental Requirements

Supply Voltage: DC 5V +indication visuelle

Storage temperature: -25°C to +45°C (-13°F to 113°F)

Temperature range: -10°C to 50°C (14°F to 122°F)

Relative Humidity: 0 to 90% non-condensing

Operating altitude: 2000m