

Arturia Audiofuse Studio

Šifra: 18066
 Kategorija proizvoda: USB Zvučne kartice
 Proizvođač: Arturia
 Channels of I/O
Cena: 106.680,00 rsd



18
 Input
 / 20

Output at 192 kHz:

Maximum Sampling Rate

192 kHz / 24-Bit

Number of Microphone Inputs

4 Preamps

Analog Audio I/O

4 x Combo XLR-1/4" TRS Input
1 x Stereo RCA Coaxial Line Input
4 x 1/4" TRS Input
4 x 1/4" TRS Insert In/Out
4 x 1/4" TRS Monitor Output
2 x 1/4" TRS Headphone Output
2 x 1/8" / 3.5 mm TRS Headphone Output

Digital Audio I/O

2 x TOSLINK Optical ADAT Input
2 x TOSLINK Optical ADAT Output
1 x RCA Coaxial S/PDIF Input (Word Clock Support)
1 x RCA Coaxial S/PDIF Output (Word Clock Support)

Host Connection	USB-C
-----------------	-------

Power Requirements	AC/DC Power Adapter (Included)
--------------------	--------------------------------

Maximum Sampling Rate	192 kHz / 24-Bit
-----------------------	------------------

Number of Microphone Inputs	4 Preamps
-----------------------------	-----------

Signal Processing

Gain/Trim Range	Line/Hi-Z Inputs: -15 dB to +36 dB Mic Inputs: 3 dB to 76 dB
-----------------	---

Connectivity

Analog Audio I/O	4 x Combo XLR-1/4" TRS Input 1 x Stereo RCA Coaxial Line Input 4 x 1/4" TRS Input 4 x 1/4" TRS Insert In/Out 4 x 1/4" TRS Monitor Output 2 x 1/4" TRS Headphone Output 2 x 1/8" / 3.5 mm TRS Headphone Output
------------------	--

Phantom Power	48 V (Selectable on Individual Inputs)
Digital Audio I/O	2 x TOSLINK Optical ADAT Input 2 x TOSLINK Optical ADAT Output 1 x RCA Coaxial S/PDIF Input (Word Clock Support) 1 x RCA Coaxial S/PDIF Output (Word Clock Support)
Host Connection	USB-C
Host Connection Protocol	USB 2.0
Sync I/O	1 x RCA Coaxial Word Clock Input (Shared with S/PDIF) 1 x RCA Coaxial Word Clock Output (Shared with S/PDIF)
MIDI I/O	1 x DIN 5-Pin Input (on Included Breakout Cable) 1 x DIN 5-Pin Output (on Included Breakout Cable)
Wireless	Bluetooth
Wireless Connectivity	Bluetooth

Performance

Frequency Response	Mic, Line, Hi-Z Inputs: 20 Hz to 20 kHz \pm 0.8 dB
--------------------	--

Maximum Input Level

Line Inputs:

+24 dBu

Mic Inputs:

+11 dBu

Hi-Z Inputs:

+18 dBu

Insert Inputs:

+18 dBu

Maximum Output Level

Insert Outputs:

+18 dBu

Outputs:

+24 dBu

Headphone Outputs:

+10 dBu

Impedance

Line Inputs:

20 Kilohm (Balanced)

10 Kilohm (Unbalanced)

Mic Inputs:

3.4 Kilohm (Mic Level)

Hi-Z Inputs:

1.1 Megohm

Aux Inputs:

20 Kilohms (Balanced)

10 Kilohms (Unbalanced)

Line Outputs:

120 Ohms (Balanced)

Headphone Outputs:

33 Ohm

Dynamic Range

Line Inputs:

117 dBA

Hi-Z Inputs:

117 dBA

Headphone Outputs:

102 dBA

THD+N

Line Inputs:

106 dBA

Mic Inputs:

104 dBA

Hi-Z Inputs:

104 dBA

Outputs:

104 dBA

Headphone Outputs:

87 dBA

EIN

Mic Inputs:
129.5 dBu

Digital Audio

Sample Rates

Up to 192 kHz (AD/DA Conversion)

Bit Depths

Up to 24-Bit (AD/DA Conversion)

Sync Sources

ADAT, S/PDIF

Compatibility

Processor Requirement

Mac:
Intel
PC:
Intel

RAM Requirements

4 GB

Storage Requirements

1 GB

Power

Power Requirements

AC/DC Power Adapter (Included)

Dimensions

10.4 x 6.3 x 2.8" / 264.2 x 160 x 71.1 mm

Packaging Info

Package Weight

6.555 lb

Box Dimensions (LxWxH)

12.7 x 8.3 x 6.4"