

Neutrik NAC3FXXB-W-S-D powerCON

Product

Šifra: 18147

Kategorija proizvoda: Konektori

Proizvođač: Neutrik

Connector series

NAC3FXXB-W

powerCON k

Cena: 900,00 rsd



Electrical

Contact resistance

≤ 2 mΩ

Dielectric strength

> 3 kVac (after mating cycles)

Insulation resistance

> 10 GΩ (initially)

Number of electrical contacts

2 + PE

Rating Europe

EN 60320-1: 16 A 250 V AC, CBC

Rating USA / Canada

cUL 60320-1: 20 A 127 V AC, CBC

Mechanical

Cable O.D.

6 - 12 mm

Lifetime

typically 5'000 mating cycles

Wiresize (mm²)

1.5 - 2.5 mm²

Wiresize (AWG)

16 - 12 AWG, see above cable list

Locking device

Twist lock

Termination

Screw type terminals

Material	
Contact plating	Ag
Contacts	Copper Alloy
Insert	Polyamide (PA6.6)
Locking element	Zinc diecast
Shell	Polyamide (PA6) / TPE
Strain relief	Polyketone
Bushing	Polypropylene / TPE

Environmental	
Temperature range	-33 °C to + 80 °C
Protection class	IP20
Flammability acc. to UL94	V-0