

Neutrik NLT4MXX

Product

Šifra: 18153

Title

Kategorija proizvoda: Konektori

Proizvođač: Neutrik

Gender

NLT

ma

Cena: 2.100,00 rsd



Electrical

Contact resistance

< 2 mΩ

Dielectric strength

2.8 kVac

Insulation resistance

>0.1 GΩ (after dampheat)

Rated current per contact

30 A rms continuous

Rated voltage

250 V ac

Attention

speakON is NOT to be used as an AC mains or power supply connector!

Mechanical

Cable O.D.

9 - 16 mm

Lifetime

> 5000 mating cycles

Wiresize

6 mm²

Wiresize

10 AWG

Termination

Solder contacts

Locking device	Quick Lock
----------------	------------

Material	
-----------------	--

Contact plating	Ag
-----------------	----

Contacts	Copper Alloy
----------	--------------

Shell	Zinc diecast, Ni plated
-------	-------------------------

Insert	Polyamide (PA 66)
--------	-------------------

Strain relief	Polyacetal (POM)
---------------	------------------

Environmental	
----------------------	--

Temperature range	-30 °C to +80 °C
-------------------	------------------

Flammability	UL 94 V-0
--------------	-----------

Protection class	IP 54 (mated condition)
------------------	-------------------------

Solderability	Complies with IEC68-2-20
---------------	--------------------------