

## Biamp - Apart Desono COLW41 White

Šifra: 18422  
Kategorija proizvoda: Outdoor Zvučnici  
Proizvođač: Biamp - Apart

Cena: **32.280,00** rsd



Operating Mode: Passive  
Operating Environment: Indoor/Outdoor  
Operating Range (-10dB): 155 Hz to 16 kHz  
Nominal Beamwidth (H x V): 100° x 15°  
Transducers: LF 4 x 3.3" (84 mm) coated paper cone / HF 1 x 1" (25 mm) soft dome  
Continuous Power Handling @ Nominal Impedance: 25V 40W @ 16Ω (160W peak)  
Nominal Sensitivity: @ 1W - 94 dB / @ 2.83V - 91 dB  
Nominal Maximum SPL: Peak 116 dB / Continuous 110 dB  
Transformer 70V: 40W, 20W, 15W, 7.5W / 100V: 40W, 30W, 15W  
Recommended Amplifiers: 40W - 80W @ 16Ω (25V - 36V)

Input Connection: Multi-position pass-through, screw-down terminal block  
Controls: None; select transformer tap or low impedance input via terminal block wiring  
Mounting Provisions: Adjustable tilt L-bracket  
Environmental: IP66 per IEC 60529  
Dimensions H x W x D: 21.9" x 3.9" x 3.3" (555 mm x 100 mm x 83 mm)  
Weight: 8.6 lbs (3.9 kg)  
Accessories (included) L-brackets and 2x IP66 water-tight gland nuts

### APPLICATIONS

Houses of Worship · Retail Outlets · Hotels  
Bars and Restaurants · Courtrooms ·  
Auditoria · Theaters · Museums · Airports  
Corporate Meeting Rooms

### DESCRIPTION

The Desono COLW41 two-way 4 x 3.3" column loudspeaker is an excellent choice when sonic clarity and predictable directional control are required from an unobtrusive loudspeaker designed to blend in with the background.

The highly-focused dispersion pattern and improved speech intelligibility of the COLW41 enables it to excel in reverberant environments like houses of worship and auditoria, while its weather-resistant construction allows it to be used in outdoor

applications such as patios or concourses  
The COLW41 utilizes a 4-position  
switchable transformer ranging from  
7.5W to 40W with low-impedance bypass  
for constant-voltage operation, making  
it an excellent choice for large areas of  
BGM.

The Desono COLW41 is an excellent  
choice for both indoor and outdoor  
distributed audio applications that need  
speech intelligibility and background  
music reproduction.