

Biamp Desono EX-S10SUB-CM-B
 Operating Mode: Passive, low impedance
Black SUBWOOFER



Operating Environment: Indoor/Outdoor
 Sifra: 18428
 Kategorija proizvoda: Nazidni Zvučnici
Operating Range (-10dB): 38 Hz to 140 Hz
 Proizvođač: Biamp - Apart

Nominal Beamwidth (H x V): Omnidirectional

Cena: 113.880,00 rsd

Transducers: LF 1 x 10" (250 mm) treble

Sensitivity @ 1 m: 89 dB (2.83 V)
 89 dB (1 W, 8 Ω nominal impedance)

Nominal Continuous Power Handling: 49 V (300 W, 8 Ω)

Nominal Maximum SPL (Processed) @ 1 m: UXO 80 Hz: Continuous 112 dB Peak 118 dB
 UXO 125 Hz: Continuous 113 dB Peak 119 dB

Rated Continuous Voltage: 39.8 V (32 dBV)

Rated Maximum SPL (Processed) @ 1 m: UXO 80 Hz: Continuous 110 dB Peak 122 dB
 UXO 125 Hz: Continuous 111 dB Peak 123 dB

Required Processing: 35 Hz, 18 dB high-pass filter; DSP preset

Recommended Amplifiers: 300 W - 600 W, 8 Ω (49 V - 69 V)

Input Connection: Lever-actuated wire clamping 4-position terminal block with pass-through

Controls: None

Mounting Provisions: ClickMount pan-tilt bracket or ClickMount U-Bracket

Compliance: ETL listed to comply with UL 1480A, CSA STD C22.2# 62368-1

Environmental Rating: IP54 per IEC 60529, IEC 60068-2-5 (Solar Radiation)
 IEC 60068-2-11 (Salt Mist), IEC 60068-2-42 (SO₂)
 IEC 60068-2-60 (Chlorine)

Dimensions H x W x D	529 mm x 310 mm x 312 mm [20.8" x 12.2" x 12.3"]
Weight (loudspeaker only)	12.8 kg [28.26 lbs]
Finish	High-impact UL94 5VB rated polycarbonate/ABS blend, painted UV resistant matte finish Bracket: Heavily reinforced glass-filled nylon with UV-resistant painted matte finish cover Color: Black (RAL 9017) or White (RAL 9016)
Grille	Powder-coated perforated Marine Grade aluminum backed with hydrophobic cloth Black or White
Models (Order by mounting option)	EX-S10SUB-CM [-B,-W] - loudspeaker with large ClickMount pan-tilt bracket EX-S10SUB-UB [-B,-W] - loudspeaker with ClickMount U-Bracket and ClickPlug
Options	CMX-LG [-B,-W] - Large ClickMount Pan-tilt Bracket Kit EXUB-S10 [-B,-W] - EX-S10 ClickMount U-Bracket kit

Description

The Desono EX-S10SUB, 10 inch subwoofer provides additional deep base to the EX-S6 or EX-S8 systems for full-range, foreground music playback. With its discreet matching enclosure, EX-S10SUB easily blends in the background of an application, making it easy to hear, but difficult to spot.

Designed for easy and fast installation, our innovative, patented ClickMount™ brackets provide installers with two distinct mounting options. The ClickMount pan-tilt bracket provides indexed aiming control and allows for mounting EX Series quickly in either vertical or horizontal orientation without moving the bracket position. The ClickMount U-Bracket is also available for low profile mounting or exterior use and includes the ClickPlug with an integrated gland nut for weather-resistant applications. Both brackets are theft and tamper resistant.

Features:

- Exceptional audio clarity with discreet styling
- Easy to install with two mounting options
- Low frequency boost for distributed applications
- ETL listed to comply with UL 1480A, CSA 62368-1, CE marked, and RoHS compliant