

FBT MITUS 210MA

Šifra: 10779

Kategorija proizvoda: Aktivne Zvučne Kutije

Proizvođač: FBT

Cena: **239.880,00** rsd



2-way bi-amplified, bass-reflex design with coaxial driver

2 x 250 mm (2 x 10") B&C custom neodymium magnet speakers with 64 mm (2.5") voice coil, one of them is coaxial with 36 mm (1.4") exit titanium compression driver and 64 mm (2.5") voice coil

Frequency response from 60Hz to 20KHz

Class D built-in amplifiers, 600WRMS to the LF and 300WRMS to the HF with switch mode power supply

DSP with 8 eq presets

Control panel with XLR input and link, volume, presets, HP-filter, ground-lift

70° conical dispersion

15 mm (5/8") birch plywood enclosure, scratch resistant black paint finish

35 mm (1.38") stand socket and back side carrying handle

Ideal for live sound stage monitoring applications, as well as a front of house main PA speaker

Very lightweight, only 19Kg

Configuration: 2 Way

Frequency response: 60Hz - 20kHz

Low frequency woofer: 2x 10" with 2.5" VC

High frequency driver: 1x 1.4" with 2.5" VC

Maximum SPL cont/peak: 127 / 134dB

Dispersion: 70 x 70 conical (HxV)

Input impedance: 22kohm

Crossover frequency: 1.2 kHz

Input connector: XLR with link out

Net Dimension (WxHxD): 547 x 290 x 402mm

Net Weight: 19kg

Transport Dimension (WxHxD): 890 x 390 x 510mm

Transport Weight: 21.2kg

AC Power requirements: 640VA

Built-in amplifier LF/HF: 600/300w RMS

Built-in amplifier peak LF/HF: 1200/600w

Power cord: 5m PowerCon

The FBT MITUS 210MA bi-amplified speaker feature 0.59" birch plywood construction; the front shall be protected by a heavy duty metal grille with anti-resonance spacers and exclusive synthetic cloth to protect the drivers and a rugged touring grade scratch resistant black paint finish protects the cabinet exterior.

The FBT MITUS 210MA is a two way coaxial design incorporating 2x 10" B&C custom neodymium magnet coaxial speaker with 2.5" voice coil and 1.4" exit titanium compression driver with 2.5" voice coil, a class D built-in amplifiers 600W RMS to the LF and 300W RMS to the HF with switch mode power supply.

The FBT MITUS 210MA provides a DSP with A/D-D/A low noise converters with 8 selectable presets.

The FBT MITUS 210MA shall meet the following performance criteria: Frequency response of 60Hz to 20kHz, Maximum SPL of 132dB, Nominal impedance 8 Ohm LF / 8 Ohm HF. The control panel provides XLR «in&link», volume, preset, HP filter, GND lift switch. A standard 1.38" speaker stand socket allows the FBT MITUS 210MA to be mounted on speaker stand.