

Mackie DLM12

Šifra: 18529
Kategorija proizvoda: Aktivne Zvučne Kutije
Proizvođač: MACKIE

Cena: 119.880,00 rsd



Class D

2,000W Peak Power
Generates up to 128dB SPL
Integrated DL2 Digital Mixer
Two Flexible Input Channels
DSP Effects, EQ and Audio Tools
Common-Magnet Design
Unpowered Audio Thru Output

PA Speaker

Configuration	Active 2-Way
Total Power Capacity	1000 W RMS 2000 W Peak
Amplifier Power Rating	LF: 500 W RMS 1000 W Peak HF: 500 W RMS 1000 W Peak
Amplifier Class	Class-D

Drivers

HF Driver	1 x 1.75" / 44 mm Polyimide Compression Driver with 1" / 25 mm Throat
LF Driver	1x 12" / 305 mm Woofer
LF Voice Coil	2.5" / 64 mm
Magnet	HF: Ferrite LF: Ferrite

Performance

Frequency Response	38 Hz to 20 kHz -10 dB
Maximum SPL	128 dB
Coverage Angle	90° H x 90° V

I/O Impedance

Mic Input:
3.3 Kilohms (Balanced)
Line Input:
20 Kilohms (Balanced)
10 Kilohms (Unbalanced)
1/4" Input:
16 Kilohms (Balanced)
8 Kilohms (Unbalanced)
XLR Line Input:
20 Kilohms (Balanced)
10 Kilohms (Unbalanced)
Hi-Z Input:
1 Megohms (Unbalanced)
RCA Input:
25 Kilohms (Unbalanced)

Total Harmonic Distortion/Noise

< 1%

Connectivity

Audio I/O

1x Combo XLR-1/4" TRS Mic/Line Input
1x Combo XLR-1/4" TRS Mic Input
1x Stereo RCA Input
1x XLR 3-Pin Thru/Output

Signal Processing

Crossover

1.6 kHz

EQ

LF Shelf:
±15 dB at 80 Hz
MF Notch/Peak:
±15 dB at 2.5 kHz
HF Shelf:
±15 dB at 12 kHz

Alignment Delay

0 to 300 ms

Power

AC Input Power

100 to 120 VAC, 50 / 60 Hz
220 to 240 VAC, 50 / 60 Hz

AC Power I/O

1x IEC

Power Consumption

250 W

Physical

Mounting

1 x Pole Socket
3 x M10

Handles

1x Top

Cooling

Fan (Variable Speed)

Construction Material

ABS, Metal Grille

Operating Temperature

32 to 104°F / 0 to 40°C

Dimensions

15.9 x 15.3 x 14.3" / 403 x 389 x 363 mm

Weight

31 lb / 14.1 kg

Packaging Info

Package Weight

37 lb

Box Dimensions (LxWxH)

20 x 20 x 19.5"