

Mackie DLM12S - Aktivni sabvufer

Šifra: 18530
 Kategorija proizvoda: Aktivni Subwooferi
 Proizvođač: MACKIE

Cena: 143.880,00 rsd

Generates up to 128dB SPL
 Frequency Response Down to 35 Hz
 DLP Digital Processor
 Precision Digital Variable Crossover
 Flexible Connectivity
 Compact Design and Durable Construction

1,000W RMS Pow
 2,000W Peak Power



Class
D

PA Speaker

Configuration	Active Subwoofer
Total Power Capacity	1000 W RMS 2000 W Peak
Amplifier Class	Class-D

Drivers

LF Driver	1x 12" / 305 mm Woofer
LF Voice Coil	3" / 76 mm
Magnet	Ferrite

Performance

Frequency Response	35 Hz to 135 Hz -10 dB
Maximum SPL	128 dB
I/O Impedance	Input: 20 Kilohms (Balanced) 10 Kilohms (Unbalanced)
Total Harmonic Distortion/Noise	< 1%

Connectivity

Audio I/O	2x XLR 3-Pin Balanced Input 2x XLR 3-Pin Balanced Output 2x XLR 3-Pin Balanced High-Pass Output
-----------	---

Signal Processing

Crossover	60 to 120 Hz
-----------	--------------

Alignment Delay	0 to 300 ms
-----------------	-------------

Power

AC Input Power	100 to 120 VAC, 50 / 60 Hz 220 to 240 VAC, 50 / 60 Hz
----------------	--

AC Power I/O	1x IEC
--------------	--------

Power Consumption	250 W
-------------------	-------

Physical

Handles	2x Side
---------	---------

Cooling	Fan (Variable Speed)
---------	----------------------

Construction Material	Metal Grille, Wood
-----------------------	--------------------

Operating Temperature	32 to 104°F / 0 to 40°C
Dimensions	17.9 x 16.4 x 20.8" / 455 x 417 x 529 mm
Weight	48 lb / 21.7 kg

Packaging Info

Package Weight	58.2 lb
Box Dimensions (LxWxH)	27.5 x 23.5 x 23"