

Art Pro Audio ART-MX524CE

Šifra: 18632
Kategorija proizvoda: Višezonske Miksete
Proizvođač: ART

Cena: **59.880,00** rsd



Overview

The **ART MX524 Five Channel Four Zone Mic/Line Mixer** is a versatile rack mount mixer that combines Five independent input channels and routes them to four zone outputs. Channels one thru four accept a balanced Line or Mic signal thru the Combo jack connector. CH5 accepts a line level signal through RCA jacks. The unit has an independent selectable +48 Volt phantom power function for channels one thru four. Channels one thru four can also accept unbalanced line-level signals. Each channel has a level control and can be routed to any zone output. Separate level, bass and treble controls adjust the sound of each input channel.

The ART MX524 may be used on stage, in the studio, or for permanent install applications including conference rooms, corporate boardrooms, churches, restaurants, small clubs, health clubs and more. A built-in power supply and triple high 19-inch rack mount format allows for easy installation and reliable long-term operation.

Key Features

- Five input channels with individual level controls using XLR/Phono jacks with master level, bass and treble controls
- Balanced Mic/Line XLR inputs for channels one thru four
- Full +48V low-noise phantom power for channels one thru four mic inputs
- Front panel 1/8-inch stereo (TRS) mini-phone plug for Headphone monitoring
- Four sets of Euro Bloc connectors for the Zone outputs
- Telephone paging function
- Dc power back up
- Separate monitor outputs
- LED VU meter on all outputs
- Rear mount RCA Line inputs for additional audio inputs
- Rugged 3U rack-mount steel chassis with built-in power supply
- Perfect for stage, studio and permanent installations

Three-year warranty

Specifications

Frequency Response 20 Hz - 22kHz \pm 2 dB

Max. Input Gain

60dB CH MIC. Input Main out (XLR, balanced)

50dB CH MIC. Input & REC. out (unbalanced)

60dB CH MIC. Input Mic. out (unbalanced)

60dB CH MIC. Input Mono out (unbalanced)

THD&N

<0.03% @1kHz

Impedance

Microphone input: 1.4k Ω

All other inputs 10k Ω or greater

Zone outputs 120 Ω

Monitor Speaker output 8 Ω

Monitor Line output 120 Ω

Phantom power

48VDC

EQ

Low: \pm 10 dB - 100 Hz

High: \pm 10 dB - 10 kHz

Zone Outputs

+26dB (Balanced)

Monitor Line Output

+15dB (Unbalanced)

Monitor speaker output

1 W rms / 8 Ω

Headphone output

0.5 W rms / 47 Ω

Connectors

Inputs: Combo XLR/¼ Jacks, RCA

Outputs: Euroblock, Screw terminals

Power Requirements USA

110~120VAC 50/60Hz or 24VDC

Export units configured for country of destination

Dimensions (HWD)

5.1-inch x 19-inch x 7.5-inch

130mm x 483mm x 191mm

Weight

6.63 lbs. (3.0 kg)