

## FBT VENTIS 110A - Aktivni zvučnik

Šifra: 18819  
Kategorija proizvoda: Aktivne Zvučne Kutije  
Proizvođač: FBT

**Cena: 103.800,00 rsd**

Net Dimension (WxHxD): 329 x 575 x 325mm  
Net Weight: 15.6kg  
Transport Dimension (WxHxD): 420 x 675 x 400  
Transport Weight: 18.1kg  
AC Power requirements: 640VA  
Built-in amplifier LF/HF: 900w (700w LF + 200w HF)  
Built-in amplifier peak LF/HF: 1800w (1400w LF + 400w HF)  
Power cord: 5m Neutrik True1  
Built in amplifier: 900w (700w LF + 200w HF)  
Built in amplifier peak: 1800w (1400w LF + 400w HF)  
Maximum SPL continuous/peak: 124/131dB  
Dispersion (HxV): 80° x 50° rotatable

### KEY FEATURES

- 2-way, bi-amplified, bass reflex design
- Biamped: 700W RMS LF and 200W RMS HF power amplifiers in Class D for LF and in Class H/AB for HF
- Digital Signal Processor with graphic display
- 15 mm (0.59") birch plywood scratch resistant enclosure and internal bracing
- High efficiency switch mode power supply
- Control Panel features balanced XLR/Jack input, XLR LINK OUT, 2 x Volume, RCA Stereo input, DSP display with rotative encoder and push
- 250mm (10") LF woofer with 50mm (2") voice coil, custom made for FBT
- 25mm (1") exit throat B&C HF compression driver with 36mm (1.4") voice coil
- Frequency response from 58Hz to 20 kHz
- 80°H x 50°V Constant Directivity Rotatable Horn
- 6 x M10 suspension points, optional wall bracket mount thread, 35mm (1 3/8") top-hat
- Speaker stand socket, one aluminium handle
- 45° monitor taper
- Adjustable delay between 0 - 10m
- Weight : 15.6Kg
- Dimensions : 329 x 575 x 325mm

### PRODUCT DESCRIPTION

PROCESSED ACTIVE SPEAKER 700W + 200W RMS - 131DB SPL

For the VENTIS range, quality and flexibility are the watchwords. Based on a powerful combination of B&C compression drivers and FBT's own custom, long excursion woofers, the 115, 112 and 110 models are two-way, bass reflex designs housed in 15mm birch plywood. A full-grille design backed by specially treated acoustic cloth delivers the characteristic style for which FBT is known, while fully rotatable constant directivity horns ensure accurate coverage.

### FBT VENTIS 110A - Aktivni zvučnik

Configuration: 2 Way  
Frequency response: 58Hz - 20kHz -6dB  
Low frequency woofer: 10" / 2" coil  
High frequency driver: 1" / 1.4" coil  
Maximum SPL cont/peak: 124/131dB  
Dispersion: 80 x 50 Rotatable  
Input impedance: 22kOhm  
Input connector: XLR/Jack Combo socket with XLR link out, RCA stereo input

## **VENTIS Presets**

The FBT VENTIS range offers powerful DSP with 6 versatile presets. Crafted by expert FBT engineers, the presets offer a performance for every requirement.

**ORIGINAL / LIVE** The renowned, smooth FBT sound

**VOCAL** A special EQ setting to maximise speech intelligibility

**DJ** Designed to keep the energy high and your audience dancing

**TOURING** The reliability and the roar of the industry's most popular touring systems

**LOUDNESS** The ultimate preset for listening at a medium or low volume

**WARM** A special setting to emphasise full-bodied, low-mid frequencies.