


FBT VENTIS 110A - Aktivni zvučnik

Šifra: 18819
Kategorija proizvoda: Aktivne Zvučne Kutije
Proizvođač: FBT

Cena: **89.880,00** rsd



Configuration: 2 Way
Frequency response: 58Hz - 20kHz -6dB
Low frequency woofer: 10" / 2" coil
High frequency driver: 1" / 1.4" coil
Maximum SPL cont/peak: 124/131dB
Dispersion: 80 x 50 Rotatable
Input impedance: 22kOhm
Input connector: XLR/Jack Combo socket with XLR link out, RCA stereo input
Net Dimension (WxHxD): 329 x 575 x 325mm
Net Weight: 15.6kg
Transport Dimension (WxHxD): 420 x 675 x 400
Transport Weight: 18.1kg
AC Power requirements: 640VA
Built-in amplifier LF/HF: 900w (700w LF + 200w HF)
Built-in amplifier peak LF/HF: 1800w (1400w LF + 400w HF)
Power cord: 5m Neutrik True1
Built in amplifier: 900w (700w LF + 200w HF)
Built in amplifier peak: 1800w (1400w LF + 400w HF)
Maximum SPL continuous/peak: 124/131dB
Dispersion (HxV): 80° x 50° rotatable

KEY FEATURES

- 2-way, bi-amplified, bass reflex design
- Biamped: 700W RMS LF and 200W RMS HF power amplifiers in Class D for LF and in Class H/AB for HF
- Digital Signal Processor with graphic display
- 15 mm (0.59") birch plywood scratch resistant enclosure and internal bracing
- High efficiency switch mode power supply
- Control Panel features balanced XLR/Jack input, XLR LINK OUT, 2 x Volume, RCA Stereo input, DSP display with rotative encoder and push
- 250mm (10") LF woofer with 50mm (2") voice coil, custom made for FBT
- 25mm (1") exit throat B&C HF compression driver with 36mm (1.4") voice coil
- Frequency response from 58Hz to 20 kHz
- 80°H x 50°V Constant Directivity Rotatable Horn
- 6 x M10 suspension points, optional wall bracket mount thread, 35mm (1 3/8") top-hat
- Speaker stand socket, one aluminium handle
- 45° monitor taper
- Adjustable delay between 0 - 10m

Weight : 15.6Kg

Dimensions : 329 x 575 x 325mm

PRODUCT DESCRIPTION

PROCESSED ACTIVE SPEAKER 700W + 200W RMS - 131DB SPL

For the VENTIS range, quality and flexibility are the watchwords. Based on a powerful combination of B&C compression drivers and FBT's own custom, long excursion woofers, the 115, 112 and 110 models are two-way, bass reflex designs housed in 15mm birch plywood. A full-grille design backed by specially treated acoustic cloth delivers the characteristic style for which FBT is known, while fully rotatable constant directivity horns ensure accurate coverage.

VENTIS Presets

The FBT VENTIS range offers powerful DSP with 6 versatile presets. Crafted by expert FBT engineers, the presets offer a performance for every requirement.

ORIGINAL / LIVE The renowned, smooth FBT sound

VOCAL A special EQ setting to maximise speech intelligibility

DJ Designed to keep the energy high and your audience dancing

TOURING The reliability and the roar of the industry's most popular touring systems

LOUDNESS The ultimate preset for listening at a medium or low volume

WARM A special setting to emphasise full-bodied, low-mid frequencies.