


FBT X-LITE 112 Pasivni zvučnik

Šifra: 18821
Kategorija proizvoda: Pasivne Zvučne Kutije
Proizvođač: FBT

Cena: **37.920,00** rsd



Recommended amplifier: 400W RMS
Long Term power: 200W
Short term power: 800W
Nominal impedance: 8Ohm
Frequency response: 55Hz - 20kHz
Low Frequency woofer: 12 - 2.5 coil inch
High frequency driver: 1 - 1.4 coil inch
Sensitivity (@1W/1m): 97dB
Maximum SPL cont/peak: 123.5 / 126.5dB
Dispersion: 90° x 60° HxV
Crossover Frequency: 1.8kHz
Recommended HP filter: HP 45Hz - 12/24dB oct.
Recommended external filter: FBT DSP Processor
Input connector: 2 x Speakon
Net Dimension (WxHxD): 356 x 619 x 357 mm / 14,01 x 24,37 x 14,05 inch
Net Weight: 16.4 Kg / 36.15 Lb

The asymmetrical shape of the FBT X-LITE 112 cabinet also allows use as a floor stage monitor. The FBT X-LITE 112 is two way design incorporating an 12" low frequency woofer and 1" HF compression driver coupled to a 90°H x 60°V constant directivity horn. With a frequency range of 55Hz - 20kHz the FBT X-LITE 112 speakers provide high fidelity sound for both speech and music applications with a maximum SPL of 126.5dB.

Ideal for small fixed installations the FBT X-LITE 112 speaker have an impedance of 8 Ohm and the internal crossover is at a fixed frequency of 1.8kHz. The control panel features 2 x NL4 Neutrik speakon. 4 x M10 rigging points built into the cabinet along with the optional mounting brackets allow the FBT X-LITE 112 speaker to be surface mounted on walls or ceilings. A standard 1,38" speaker stand socket allows the FBT X-LITE 112 to be mounted on speaker stand. A front face steel grille protects the speaker from external damage.