

Neutrik NP3RX-B

Šifra: 18905
Kategorija proizvoda: Konektori
Proizvođač: Neutrik

Cena: 800,00 rsd



The
heavy
duty

professional phone e design of the existing C series by offering the thinnest available A-gauge 1/4" plug with unique Neutrik chuck type strain relief on the market. The slimline shell with a width of 14.5 mm meets the most recent requirements for highest density jackfields (15.88mm jack pitch).

The precise machined one-piece tip contact without rivets makes it unique and avoids hook up in a socket or break off the tip.

The Plug X Series serves all applications such as guitar applications, audio cables, snakes, speakers, amplifiers and mixing desks.

All metal housing eliminates the plastic cover of the predecessor NP*RCS and improves further durability and EMI protection

- Extra slim 1/4" plug for highest packing density
- Robust diecast shell in stylish design
- Proven chuck type strain relief for reliable cable retention
- Sleek design for best handling convenience
- Precision machined one-piece contacts - avoid hook up of tip contact

Electrical

Contact resistance depends on mating connector $m\Omega$
Dielectric strength 1 kVdc
Insulation resistance $> 2 G\Omega$ (initial)
Rated current per contact depends on mating connector A
Rated voltage $< 50 V$

Mechanical

Cable O.D. 4 - 7 mm
Lifetime > 1000 mating cycles
Wiresize 1 mm²
Wiresize 18 AWG
Wiring Solder contacts

Material

Bushing Polyacetal (POM) + PU
Contact plating 0.2 μm Au
Contacts Brass (CuZn39Pb3)
Insert Polyamide (PA 6.6 30 % GR)

Shell Zinc diecast (ZnAl4Cu1)
Shell plating KTL coating
Strain relief Polyacetal (POM)

Environmental

Standard compliance IEC 60603-11 / EIA RS-453
Solderability Complies with IEC 68-2-20
Temperature range -20 °C to +65 °C