

Zoom H2essential

Šifra: 19362
Kategorija proizvoda: Snimači/Rekorderi
Proizvođač: ZOOM

Cena: 21.480,00 rsd



• Mid-Side

stereo pickup fro

- Pickup pattern selection: 120°, 90°, and MONO

- 32-bit float recording requires no gain adjustment
- 3.5mm stereo mini external mic/line input
- 3.5mm stereo mini line/headphone output
- Built-in speaker for quick preview
- Built-in Mixer for volume adjustments
- Color 1.3-inch LCD display
- Low-cut filter
- Accessibility for the visually impaired
- 32-bit float USB mic functionality for Win/Mac/iOS/Android
- Remote control from iOS app via BTA-1 Bluetooth connection
- Micro SDHC / micro SDXC cards up to 2TB supported
- Powered by 2 AA batteries, AC adapter, or USB mobile battery
- 11 hours of operation with 2 AA alkaline batteries

Inputs

MID mic (FRONT/REAR)

Pickup pattern: Unidirectional

Sensitivity: -37 dB/Pa at 1 kHz

Maximum sound pressure input: 120 dB SPL

SIDE mic

Pickup pattern: Bidirectional

Sensitivity: -39 dB/Pa at 1 kHz

Maximum sound pressure: 122 dB SPL

MIC/LINE IN jack

Connector: Stereo mini jack

Input impedance: 2 kΩ

Maximum input level: -7 dBu

Plug-in power: 3.3 V

Outputs

PHONE/LINE OUT jack

Connector: Stereo mini jack

Maximum output level: 20 mW + 20 mW (when 32 Ω load)

Output impedance: 10 Ω or less

Built-in speaker

Type: 20 mm × 30 mm elliptical dynamic speaker

Effective maximum output: 250 mW

Recorder

Recording format:

- WAV
- 44.1, 48 or 96 kHz / 32-bit float
- Stereo / mono
- BWF and iXML formats supported

Recording media

- microSDHC memory cards
- microSDXC memory cards

Display

1.3" full-color LCD: 240 × 240

USB

Connector:

- USB Type-C
- Use a USB cable that supports data transfer.

Audio interface:

- USB2.0 High Speed
 - Input and output channels:
4 in / 2 out (Multi)
2 in / 2 out (Stereo)
 - Sampling frequencies:
44.1/48/96 kHz (audio interface only)
44.1/48 kHz (audio interface + onboard recording)
- Bit depths:
- 24-bit, 32-bit float
- File transfer: USB2.0 High Speed

Power

2 AA batteries: Alkaline, Lithium, or Rechargeable NiMH

AC adapter:

- ZOOM AD-17: DC 5 V/1 A
- USB bus power is supported.