

BEYERDYNAMIC DT 770 PRO 250 ohm - Studijske slušalice

Šifra: 9273

Kategorija proizvoda: Slušalice

Proizvođač: Beyerdynamic

Cena: 16.299,00 rsd



FEATURES

- Closed diffuse field studio headphones
- Innovative bass reflex system
- Robust spring steel headband
- Single-sided cable
- Soft headband pad
- Gold plated mini stereo jack plug (3.5 mm) & 1/4" adapter (6.35 mm)

APPLICATIONS

The DT 770 PRO is a closed, dynamic headphone for professional use as a monitoring headphone in studios. Its design has been tailored for use in a studio.

The single-sided cable makes it easier to handle the headphones when they have to be constantly put on and taken off. The robust spring steel construction gives the headphones a secure fit and the mechanical reliability needed for daily use.

Soft, adjustable ear cups and a single-sided cable contribute to a high level of long-term comfort.

The connecting cable is fitted with a gold-plated mini stereo jack plug (3.5 mm) with a 1/4" adapter (6.35 mm) and can therefore be connected to all common headphone outputs.

With its impulse behaviour, the DT 770 PRO comes close to electrostatic headphones and delivers a natural and balanced sound. Even the deepest bass is reproduced with clarity and punch. High frequencies are converted into an analytical, clear and differentiated sound that does not produce screaming or shrieking even with powerful treble sounds.

VERSIONS

- DT 770 PRO Dynamic headphones,
32 Ω Order # 483.664
DT 770 PRO Dynamic headphones,
80 Ω Order # 474.746
DT 770 PRO Dynamic headphones,

TECHNICAL SPECIFICATIONS

Transducer type. Dynamic
Operating principle. Closed
Nominal frequency response. 5 - 35,000 Hz
Nominal impedance. 32 Ω / 80 Ω / 250 Ω
Nominal SPL. 96 dB
Nominal T.H.D.. < 0.2%
Power handling capacity. 100 mW
Sound coupling to ear. Circumaural
Ambient noise isolation
32 Ω version. approx. 20 dBA
80 Ω / 250 Ω version. approx. 18 dBA
Nominal headband pressure approx. 3.5 N
Weight
32 Ω version. 325 g
80 Ω version. 345 g
250 Ω version. 380 g
Length and type of cable. 1.6 m / straight cable (32 Ω)
3 m / straight cable (80 Ω)
3 m / coiled cable (250 Ω)
Connection. Gold plated mini stereo
jack plug (3.5 mm)
& 1/4" adapter (6.35 mm)