

FBT VERTUS CLA 406A B-Stock

Šifra: 12034
 Kategorija proizvoda: Aktivne Zvučne Kutije
 Proizvođač: FBT

Cena: **191.880,00** rsd

Compared to a traditional two-way speaker, the sound is distributed in a much more uniform manner into the listening area, regardless of whether the application is indoors, outdoors or acoustically difficult in terms of reverberation. The cylindrical wave front of the CLA projects sound forwards in a very precise and coherent fashion without the reverberant performance that is typical of conventional speakers which can excite environmental reflections, directing acoustic energy where it is not needed, especially towards the ceiling and floor. Even acoustic feedback such as that generated by microphones is rejected to a far greater extent than a conventional enclosure.

Finally, the columns narrow dimensions allow the discreet, unobtrusive integration of the column into any environment.

The qualities of the system CLA can be summarized as:

High-end sound quality with a **frequency response of 33Hz to 20kHz**, designed specifically for live

Improved dispersion within a set listening area plus extended projection

Portability and modularity – elements can be rapidly daisy-chained via a quick release system, extending both the vertical directivity and sound pressure level

Wide horizontal dispersion

High
the tr
Desig
most
ensur
speak

VERTUS CLA 406A

600W + 300W

133 dB SPL

Active Column Line Array

2-way bi-amplified line array column system

4 x 165mm (6.5") custom woofer voice coil 38mm (1.5")

Waveguide FBT large format with dispersion 100 ° H x 25 ° V

Amplifiers **Class D 600Wrms for LF and HF 300Wrms** with switching power supply

Control Panel with XLR input and link, volume, presets, filter-HP, ground-lift

12mm (1/2") birch plywood with scratch-resistant coating.

Top side tilted 10 ° for the inclination of two columns without damaging gap between the waveguides for a wavefront extremely consistent over the 18kHz

B&C
and 6
Freque

Proce

Neut

12 at
optio
hang
35mm
10 °

It is ideal for live applications, assisted by sub **CLA 118SA**, which for fixed installations

| | |
|--------------------------------|---------------|
| Built-in amplifier LF/HF: | 600/300 W RMS |
| Built-in amplifier peak LF/HF: | 1200/600 W |

| | |
|------------------------------|--|
| Frequency response: | 65Hz - 20KHz -6dB |
| Low frequency woofer: | 4x6.5 - 1.5 coil inch |
| High frequency driver: | 1x1.4 - 2.5 coil - neodymium inch |
| Maximum SPL cont/peak: | 133 dB |
| Dispersion: | 100°x25° H x V |
| Input impedance: | 22 Kohm |
| Crossover frequency: | 1.2 KHz |
| Ac power requirements: | 640 VA |
| Input connector: | XLR with loop |
| Power cord: | 5 / 16.4 mm/inch |
| Net Dimension (WxHxD): | 190x1235x290 / 7.48x44.68x11.41 mm/inch |
| Net weight: | 27 / 59.52 kg/lb |
| Transport Dimension (WxHxD): | 290x1235x390 / 11.41x48.62x15.35 mm/inch |
| Transport weight: | 32 / 70.54 kg/lb |