

FBT Mitus 118SA - Aktivni vufer

Šifra: 10311
 Kategorija proizvoda: Aktivni Subwooferi
 Proizvođač: FBT

Cena: **191.880,00** rsd

1200W 139dB SPL Processed Active Subwoofer

The MITUS 118 SA is single 18" active subwoofer equipped with a B&C neodymium magnet custom woofer. The birch-ply enclosure is designed to the same width size of the MITUS 206 LA line array, like the MITUS 121 SA, 21" active sub and the MITUS 212 FSA flying active sub. This model has a band-pass design providing more "kick" to the low frequencies, extended down to 36 Hz. The built-in amp is engineered in Class D with DSP and supplies 1200 Wrms of continuous power. A switch mode power supply guarantees the maximum energy and dynamics to the transducer.

THE FBT MITUS - Setting a New Milestone

Advancing the concept of line arrays in terms of power, performance, weight, flexibility and ease of use, the new MITUS sound reinforcement series is the true result of our experience and passion for excellence.

A comprehensive range of line array systems, speakers, subwoofers and monitor systems, available in active or passive design, to deliver the finest sound in all applications, from touring to permanent installation. Die-cast aluminum chassis. New aluminum die-cast carrying handles. Heavy duty metal grille with anti-resonance spacers and FBT exclusive synthetic cloth.

High quality B&C manufactured f compression d amplifiers mod 5 different conf stacked. A wide range extreme presets.

Mitus 118SA

FEATURES

1200W - 139dB SPL Processed Active Subwoofer

Compact vented band pass subwoofer design enclosure
 Frequency response from 36Hz to 100Hz

460 mm (18") d
 Class D amplifi

Switch mode power supply

DSP with 8 pre

Control panel with XLR input and link, volume, presets,

18 mm (3/4") b

delay, phase 0°-180°, groundlift

black paint

Eight M10 fly points, M20 top mount stand socket and two

Optional 4 swiv

FBT design aluminum handles

Perfect low-frequency extension for the MITUS range and an ideal companion for the MITUS 206LA line array for ground stack applications with optional MTB206 metal base

SPECS

1200w RMS : Class D amp w/ switch mode Power Supply

Frequency Response : 36Hz-100Hz @-6dB

Maximum SPL

Dimensions : 24"wx24.75hx30.4"d

Net Wt. : 103 L

Depth : 28.7 in

Depth : 730 mm

Height : 23.4 in

Height : 594 mm

Width : 22.6 in

Width : 574 mm

Product Weight : 103.6 lbs
Shipping Weight : 123.9 lbs
Current Draw : 640 Watt

Product Weight : 103.6 lbs
Shipping Weight : 123.9 lbs
SPL Max : 139

image not found or type unknown



Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.