

## FBT PROJECT 550BT - Nazidni zvučnik

Šifra: 10891  
Kategorija proizvoda: Nazidni Zvučnici  
Proizvođač: FBT

**Cena: 14.280,00 rsd**



Recommended  
Long Term Power: 50w

Short Term Power: 200w  
Transformer: 15-25-40-50W  
Sensitivity (1W/1m): 98dB  
Recommended HP filter: 50Hz - 24dB Oct.

PROJECT sound speakers have been created and designed in Italy. Their exclusive design characterises a complete new family of loudspeakers in the Audio Contractor range. They are ideal for any installation: their design allows the loudspeakers to be used in any environment, keeping the same high quality sound throughout. The PROJECT range utilises a compact two-way system guaranteeing high performances, wide dynamics, high fidelity sound reproduction and high voice intelligibility. PROJECT speakers are equipped with an exclusive fully adjustable support bracket for easy installation, to cut costs and save installation time the bracket may be attached to the wall prior to installing the loudspeaker and is provided with a safety cable. Connection to the loudspeakers is via plug in "Euroblock" connector and adjustment of loudspeaker output is made via screwdriver adjustable switch.

### KEY FEATURES

Bracket included  
Grey or black ABS loudspeaker  
2 way bass reflex  
5" woofer and 0.75" tweeter  
100V line transformer(Multi Tap)  
Frequency response @-10dB 85Hz-20kHz  
Dispersion HxV 100°x100°  
High-pass filter recommended 55Hz-24dB/oct  
30W/60W nominal/maximum power  
50W/100W nominal/maximum power  
Setting: 15/25/40/50W/8ohm  
Sensitivity 89dB  
Max SPL 109dB  
Specifications:

Code: 29255 BT / 32369 WHT  
Configuration: 2 way  
Recommended amplifier: 100 W RMS  
Long Term power: 50 W

Short term power: 200 W  
Transformer: 15-25-40-50 V  
Nominal impedance: 8 ohm  
Frequency response: 50Hz - 20KHz -6dB  
Low Frequency woofer: 5 inch  
Sensitivity (@1W/1m): 98 dB  
Maximum SPL cont/peak: 109 dB  
Dispersion: 100x100 HxV  
Recommended HP filter: 50Hz-24dBoct  
Input connector: Euroblock  
Net Dimension (WxHxD): 168x240x180 mm/inch