

## FBT SUBLINE 112SA - Aktivni vufer

Šifra: 12446  
 Kategorija proizvoda: Aktivni Subwooferi  
 Proizvođač: FBT

**Cena: 101.880,00 rsd**



Bass-reflex design with high SPL and punch

Frequency response from 40Hz to 140Hz

Digital Signal processor with 8 presets, 2 equalization with 2 LPF Crossover settings, cardioid configuration

15 mm (0.59") birch plywood scratch resistant enclosure with internal bracing

320mm (12.6") high excursion magnet motor with 75mm (3") voice coil

New amplifier engineered and manufactured by FBT, 700W RMS LF in Class D

Control panel with Stereo XLR in/out, Volume, EQ presets, 8 steps Delay from 0.25m to 3.5m, Phase Reversal Switch 0°-180°, 3 status LED indicators

M20 (20mm) top mount speaker stand socket and two aluminum ergonomic FBT handles

[Specific](#)

Code:	41223
Configuration:	1 way
Built-in amplifier LF/HF:	700 W RMS
Built-in amplifier peak LF/HF:	1400 W
Frequency response:	42Hz - 140Hz -6dB
Low Frequency woofer:	12 - 2.5 coil inch
Maximum SPL cont/peak:	129/133 half-space dB
Dispersion:	omnidirectional HxV
Input impedance:	22 Kohm
Crossover Frequency:	90 or 140Hz KHz
AC Power requirements:	640 VA
Input connector:	stereo XLR with loop, HP out
Power cord:	5/16.4 m/ft
Net Dimension (WxHxD):	430x447x480 / 16.9x21.5x18.9 mm/inch
Net Weight:	23./50.7 kg/lb
Transport Dimension (WxHxD):	530x547x580 / 20.9x21.5x22.8 mm/inch
Transport Weight:	27/59.5 Kg/lb