


## FBT VENTIS 112A - Aktivni zvučnik

Šifra: 12039  
Kategorija proizvoda: Aktivne Zvučne Kutije  
Proizvođač: FBT

**Cena: 125.880,00 rsd**



### VENTIS Presets

The FBT VENTIS range offers powerful DSP with 6 versatile presets. Crafted by expert FBT engineers, the presets offer a performance for every requirement.

- ORIGINAL / LIVE The renowned, smooth FBT sound
- VOCAL A special EQ setting to maximise speech intelligibility
- DJ Designed to keep the energy high and your audience dancing
- TOURING The reliability and the roar of the industry's most popular touring systems
- LOUDNESS The ultimate preset for listening at a medium or low volume
- WARM A special setting to emphasise full-bodied, low-mid frequencies.

### KEY FEATURES

- 2-way, bi-amplified, bass reflex design
- Biamped: 700W RMS LF and 200W RMS HF power amplifiers in Class D for LF and in Class H/AB for HF
- Digital Signal Processor with graphic display
- 15 mm (0.59") birch plywood scratch resistant enclosure and internal bracing
- High efficiency switch mode power supply
- Control Panel features balanced XLR/Jack input, XLR LINK OUT, 2 x Volume, RCA Stereo input, DSP display with rotative encoder and push
- 320mm (12") LF woofer with 64mm (2.5") voice coil, custom made for FBT
- 25mm (1") exit throat B&C HF compression driver with 36mm (1.4") voice coil

Frequency response from 48Hz to 20 kHz

80°H x 50°V Constant Directivity Rotatable Horn

6 x M10 suspension points, optional wall bracket mount  
thread, 35mm (1 3/8") top-hat

Speaker stand socket, two aluminium handles

45° monitor taper

Adjustable delay between 0 - 10m

Weight : 20.6Kg

Dimensions : 387 x 665 x 380mm

Configuration:

2 Way

Frequency response:

42Hz - 20kHz -6dB

Low frequency woofer:

12

High frequency driver:

1

Maximum SPL cont/peak:

126/133dB

Dispersion:

80 x 50 rotatable

Input impedance:

22kOhm

Input connector:

XLR/Jack Combo socket with XLR link out, RCA stereo input

Net Dimension (WxHxD):

387 x 665 x 380mm

Net Weight:

20.6kg

Transport Dimension (WxHxD):

500 x 765 x 470mm

Transport Weight:

23.1kg

AC Power requirements:

640VA

Built-in amplifier LF/HF:

900w (700w LF + 200w HF)

Built-in amplifier peak LF/HF:

1800w (1400w LF + 400w HF)

Power cord:

5m

Built in amplifier:

900w (700w LF + 200w HF)

Built in amplifier peak:

1800w (1400w LF + 400w HF)

Maximum SPL continuous/peak:

126/133dB

Dispersion (HxV):

80° x 50° rotatable