

## FBT VENTIS 115A - Aktivni zvučnik

Šifra: 12453

Kategorija proizvoda: Aktivne Zvučne Kutije

Proizvođač: FBT

Cena: **137.880,00** rsd

### VENTIS Presets

The FBT VENTIS range offers powerful DSP with 6 versatile presets. Crafted by expert FBT engineers, the presets offer a performance for every requirement.

**ORIGINAL / LIVE** The renowned, smooth FBT sound

**VOCAL A** special EQ setting to maximise speech intelligibility

**DJ** Designed to keep the energy high and your audience dancing

**TOURING** The reliability and the roar of the industry's most popular touring systems

**LOUDNESS** The ultimate preset for listening at a medium or low volume

**WARM** A special setting to emphasise full-bodied, low-mid frequencies.

### KEY FEATURES

2-way, bi-amplified, bass reflex design

Biamped: 700W RMS LF and 200W RMS HF power amplifiers in Class D for LF and in Class H/AB for HF

Digital Signal Processor with graphic display

15 mm (0.59") birch plywood scratch resistant enclosure and internal bracing

High efficiency switch mode power supply

Control Panel features balanced XLR/Jack input, XLR LINK OUT, 2 x Volume, RCA Stereo input, DSP display with rotative encoder and push

380mm (15") LF woofer with 64mm (2.5") voice coil, custom made for FBT

25mm (1") exit throat B&C HF compression driver with 44mm (1.7") voice coil

Frequency response from 42Hz to 20KHz

80°H x 50°V Constant Directivity rotatable Horn

6 x M10 suspension points, wall bracket mount thread,  
35 mm (1 3/8") top-hat speaker stand socket, two  
aluminium handles  
45° monitor taper  
Adjustable delay between 0 - 10m  
Weight : 25Kg  
Dimensions : 427 x 765 x 420mm

Configuration:

2 Way

Frequency response:

42Hz - 20kHz -6dB

Low frequency woofer:

15

High frequency driver:

1

Input impedance:

22kOhm

Input connector:

XLR/Jack Combo socket with XLR link out, RCA stereo input

Net Dimension (WxHxD):

427 x 765 x 420mm

Net Weight:

25kg

Transport Dimension (WxHxD):

600 x 865 x 520mm

Transport Weight:

29kg

AC Power requirements:

640VA

Power cord:

5m

Built in amplifier:

900w (700w LF + 200w HF)

Built in amplifier peak:

1800w (1400w LF + 400w HF)

Maximum SPL continuous/peak:

127/133dB

Dispersion (HxV):

80° x 50° rotatable