

## JB SECURITY DVR 4H264

Šifra: 5685  
Kategorija proizvođača: Kamere  
Proizvođač: JB SECURITYCena: **9.360,00** rsd

| <b>DVR (4H264)</b>         |   |
|----------------------------|---|
| Video System               | NTSC / PAL  |
| Operation System           | Linux   |
| Video Input / Output       | BNC 4-channel inputs / 2-channel outputs                |
| Audio Compression          | 8kHz*16bit ADPCM  |
| Audio Input / Output       | RCA 4-channel inputs / 2-channel outputs                |
| Display Frame Rate         | NTSC: 120 fps / PAL: 100 fps                            |
| Playback Resolution        | PAL: CIF(352x288), HD1(704x288), D1(704x576)            |
|                            | NTSC: CIF(352x240), HD1(704x240), D1(704x480)           |
| Total Recording Frame Rate | PAL: 25fps@D1, 50fps@HD1, 100fps@CIF                    |
|                            | NTSC: 30fps@D1, 60fps@HD1, 120fps@CIF                   |
| Recording Mode             | Always / schedule / motion detection / sensor triggered |
| Recording Pack Time        | 15/30/45/60mins selectable                              |
| HDD Interface              | Support SATA HDD & USB disk                             |
| Network Interface          | RJ45, 10M/100M  |
| Network Protocol           | Support TCP/IP, UDP, DHCP, DNNS, PPPoE                  |
| Network Function           | Support to live view with IE & with Mobile phone        |
| USB2.0                     | USB mouse, USB disk (backup, upgrade)                   |
| Playback Mode              | Normal play, fast forward, fast rewind, frame by frame  |
| PTZ                        | Built-in RS-485 port, support PELCO-P & PELCO-D         |
| Backup                     | USB flash disk, USB disk, USB CD/DVD-RW & Network       |
| PTZ Control                | Built-in RS485, support PELCO-P & PELCO-D               |
| Alarm Mode                 | Motion, Sensor, video loss, HDD error, HDD full         |
| Senor & Alarm I/O          | 4 sensor inputs / 1 alarm output                        |
| Power Supply               | DC 12V/3A (power adaptor included)                      |

|                     |                      |
|---------------------|----------------------|
| Power Consumption   | 10~15W               |
| Working Temperature | -10°C to +40°C       |
| Working Humidity    | 10% to 90%           |
| Dimension           | 300x220x47mm (WxDxH) |