

KEF Ci115QCT - Plafonski zvučnik B-Stock

KEF Ci115QCT - Plafonski zvučnik B-Stock

Šifra: 6482
Kategorija proizvoda: Plafonski Zvučnici
Proizvođač: KEF

Cena: **19.080,00** rsd

Raymond Cooke (BBC inženjer elektronike, tehnički direktor Wharfedale-a) i poslovni saradnici, osnovali su kompaniju KEF Electronics Ltd., sa namerom da prave inovativne zvučnike koristeći najnovije materijale i tehnologije. Osnovana je u Kentu 1961. godine, na imanju nekadašnje kompanije [] [] [] [] Inženjerstva i Livnice (Kent Engineering and Foundary) a odakle je [] [] [] [] A i dobio ime. Zahvaljujući stalnom eksperimentisanju sa novim materijalima i tehnologijama KEF zvučnici su uvek imali fantastična akustična merenja i mogli su da reprodukuju snimke najbliže moguće originalnom zvuku u studiju ili nastupu uživo. Od početka, kao i danas, KEFova inovativnost i kvalitet su neosporni, tako da više od pola veka unazad audiofili širom sveta uživaju u ovim zvučnicima visokih performansi.

configuration, the Ci115QCT disperses the soundfield more evenly and over a far wider area than is possible with conventional speakers. This gives you a far greater freedom of positioning, so problematic installations are no longer an issue. The compactness of its 115mm (4.5in.) Uni-Q array endows the Ci115QCT with capabilities out of all proportion to its modest size, generating an expansive, accurate and sumptuously detailed sound image. With back can, 70V/100V multi-tap transformers for distributed line systems and UL2043 safety approval for use in plenum spaces and UL1480-5 for fire protection signalling systems, it meets the highest specification requirements for interior use. The bezels and grilles can be finished to blend unobtrusively with the décor – and with KEF’s ingeniously simple fixing system, the units are exceptionally easy to install. The Ci115QCT is supplied with accessories for suspended ceiling applications.

Applications:

The Ci Commercial Series Ci115QCT is best suited where high quality music and speech reinforcement applications require hi-fi performance such as:

Multi Room systems

Home Theatre systems

Loung

Boardrooms & Offices

Airpo

Live Theatre/Concert Hall fill-in

House

Sports Arenas

| | |
|---|---|
| Model | Ci115QCT |
| Nominal Impedance | 8Ω |
| Sensitivity (2.83V @ 1m) | 86dB |
| Frequency Response +/-6dB 2pi/open-backed | - |
| Frequency Response +/-6dB With back can/rear enclosure | 70 - 20kHz |
| Crossover Frequency | 2.3kHz |
| Drive Units (LF / HF) | 115mm / 19mm |
| Recommended Amplifier Power | 15-80W |
| Features | Uni-Q Array / UL2043 & UL1480-5 approved / 80hm or 70V: 4w, 8w, 15w, 30w / 100V: 8w, 16w, 30w |
| Product External Dimensions (Diameter / Depth) | 220mm (8.66in.) / 160mm (6.30in.) |
| Cut-out Dimension (Diameter) | 196mm (7.72in.) |
| Mounting Depth from Surface (Product only / With back can) | - / 157mm (6.18in.) |