

KEF Ci160QCT - Plafonski zvučnik

Šifra: 6484
Kategorija proizvoda: Plafonski Zvučnici
Proizvođač: KEF

Cena: **26.280,00** rsd

Ci160QCT

The Ci160QCT is one of the stars of the range, thanks to its 160mm (6.5in.) Uni-Q® driver array. As the latest incarnation of KEF's patented technology, the Uni-Q 'point-source' driver configuration, it disperses the soundfield more evenly and over a far wider area than is possible with conventional speakers. Apart from being more pleasurable to listen to, this allows unprecedented freedom of positioning without compromising sound quality. What occupants experience is a richer, more accurate three-dimensional sound image that's as clean, satisfying and seamlessly integrated as the appearance of the units themselves. With back can, 70V/100V multi-tap transformers for distributed line systems and UL2043 safety approval for use in plenum spaces and UL1480-5 for fireprotection signalling systems, the Ci160QCT meets the highest specification requirements for interior use. The bezels and grilles can of course be finished to blend unobtrusively with the décor -and with KEF's ingeniously simple fixing system, the units are exceptionally easy for the contractor to install. The Ci160QCT is supplied with accessories for suspended ceiling applications. Like all KEF loudspeakers, the Ci160QCT combines innovative design with engineering integrity, with all that implies for hassle-free long term use. More sophisticated technologies. More consistency. More value. And much more natural sound.

Applications:

The Ci Commercial Series Ci160QCT is best suited where high quality music and speech reinforcement applications require hi-fi performance such as:

Multi Room systems

Home Theatre systems

Loung

Boardrooms & Offices

Airpo

Live Theatre/Concert Hall fill-in

Hous

Sports Arenas

| | |
|---|--|
| Model | Ci160QCT |
| Nominal Impedance | 8Ω |
| Sensitivity (2.83V @ 1m) | 89dB |
| Frequency Response +/-6dB 2pi/open-backed | - |
| Frequency Response +/-6dB With back can/rear enclosure | 60 - 20kHz |
| Crossover Frequency | 2.8kHz |
| Drive Units (LF / HF) | 160mm / 19mm |
| Recommended Amplifier Power | 10-100W |
| Features | Uni-Q Array / UL2043 & UL1480-5 approved / 80ohm or 70V: 8w, 15w, 30w, 60w / 100V: 16w, 30w, 60w |
| Product External Dimensions (Diameter / Depth) | 275mm (10.83in.) / 188mm (7.40in.) |
| Cut-out Dimension (Diameter) | 240mm (9.45in.) |

Mounting Depth from Surface (Product only / With back can)

- / 185mm (7.28in.)