

MARTIN AUDIO Blackline X15 - Pasivni zvučnik

Šifra: 11771

Kategorija proizvoda: Pasivne Zvučne Kutije

Proizvođač: Martin Audio

Cena: 129.880,00 rsd



Featu

High po
way sys
Symme
plywoo
User-ro
horn
Vertical
orienta
Screw-f
perfora
Integra
Pole-me
clean li
8Ω nom
Twin NL
Flexible
via M8

The loudspeaker shall be a passive, two-way system. Its transducers shall consist of a reflex-loaded 15" low frequency driver and a 1.7" diaphragm/1" exit compression driver mounted on a high frequency horn which shall be user-rotatable to enable vertical or horizontal orientation of the enclosure.

Horizontal dispersion shall be 80° and vertical dispersion shall be 50°. The on-axis frequency response shall be 55Hz-20kHz +/- 3dB and the loudspeaker shall produce a maximum SPL of 131dB peak calculated at 1 metre. Power handling shall be 400W AES, 1600W peak. Rated impedance shall be 8 ohms.

The rear connector panel shall be fitted with two NL4 type connectors. Low and high frequency sections shall be integrated by an internal 2.2kHz passive network. For optimal performance the loudspeaker shall be operated in conjunction with a dedicated electronic controller.

The symmetrical, multi-angle enclosure shall be made from plywood and finished with a black textured paint. Optional white and RAL colour finishes shall be available to special order. The enclosure shall be fitted with a pole-mount socket and M8 threaded inserts to accommodate eyebolt suspension and a wall bracket. The drivers shall be protected by a perforated steel grille with scrim cloth backing.

Dimensions (W x H x D) shall be 427mm x 690mm x 419mm (16.8in x 27.2in x 16.5in). Weight shall be 24kg (52.9lbs).

The loudspeaker shall be the Martin Audio Blackline X15.

[Links guide](#)

[Brochure](#)

[Datasheet](#)

[Measurement Data](#)

[Settings \[v3.6\]](#)