

MARTIN AUDIO CDD5W - Nazidni zvučnik

Šifra: 13067

Kategorija proizvoda: Nazidni Zvučnici

Proizvođač: Martin Audio

Cena: 35.880,00 rsd

application. Horizontal dispersion shall vary from 120° to 90° and vertical dispersion shall be 80°. The on-axis frequency response shall be 100Hz-20kHz +/- 3dB and the loudspeaker shall produce a maximum SPL of 116dB peak calculated at 1 metre. Power handling shall be 100W AES, 400W peak. Rated impedance shall be 8 ohms.

The input connector shall be a low-profile 13A push-lock type. Low and high frequency sections shall be integrated by an internal 2.5kHz passive network. For optimal performance the loudspeaker shall be operated in conjunction with a dedicated electronic controller.

The enclosure shall be made from ABS material and fitted with threaded inserts for wall and ceiling mounting. The drivers shall be protected by a perforated steel grille with scrim cloth backing.

Dimensions (W x H x D) shall be 160mm x 230mm x 149mm (6.3in x 9.1in x 5.9in). Weight shall be 2.7kg (6lbs).

The loudspeaker shall be the Martin Audio CDD5.

Features

- Ultra-Compact, CDD™ passive two-way system
- Elegant ABS moulded enclosure
- Vertical and horizontal mounting options
- 8Ω nominal impedance
- Black or white standard colour options

MARTIN AUDIO CDD5W - Nazidni zvučnik

**Martin
Audio**

CDD5

The loudspeaker shall be a passive, two-way system utilising Coaxial Differential Dispersion technology. Its transducers shall consist of a reflex-loaded 5.25" low frequency driver and a coaxially-mounted 0.75" dome high frequency driver loaded by a static waveguide that merges with moving waveguides added to the cone of the low frequency driver to define the HF horn geometry.

The coaxial driver shall be user-rotatable to enable vertical or horizontal operation as required by the

Coaxial Differential Dispersion™ technology

User-rotatable coaxial drive unit

Screw-free perforated steel grille

Discreet mounting accessories

70V/100V line transformer option

PIN CONNECTIONS	Left to right: Input+, Input -, Link -, Link +
FITTINGS	6 x M5 inserts for wall/ceiling brackets
DIMENSIONS	(W) 160mm x (H) 230mm x (D) 149mm (W) 6.3ins x (H) 9.1 ins x (D) 5.9 ins
WEIGHT	3kg (6.6lbs)