

MARTIN AUDIO CDD8B Nazidni zvučnik

MARTIN AUDIO CDD8B - Nazidni zvučnik

Šifra: 13107

Kategorija proizvoda: Nazidni Zvučnici

Proizvođač: Martin Audio

Cena: **71.880,00** rsd

Martin Audio CDD8

The loudspeaker shall be a passive, two-way system utilising Coaxial Differential Dispersion technology. Its transducers shall consist of a reflex-loaded 8" low frequency driver and a coaxially-mounted 1" exit high frequency compression driver loaded by a static waveguide that merges with moving waveguides added to the cone of the low frequency driver to define the HF horn geometry.

The coaxial driver shall be user-rotatable to enable vertical or horizontal operation as required by the application. Horizontal dispersion shall vary from 110° to 80° and vertical dispersion shall be 60°. The on-axis frequency response shall be 70Hz-20kHz +/- 3dB and the loudspeaker shall produce a maximum SPL of 123dB peak calculated at 1 metre. Power handling shall be 200W AES, 800W peak. Rated impedance shall be 8 ohms.

The input connector shall be a low-profile 13A push-lock type. Low and high frequency sections shall be integrated by an internal 2.3kHz passive network. For optimal the loudspeaker shall be operated in conjunction with a dedicated electronic controller.

The enclosure shall be made from rigid composite material and fitted with threaded inserts for wall and ceiling mounting. The drivers shall be protected by a perforated steel grille with scrim cloth backing. Dimensions (W x H x D) shall be 256mm x 410mm x 252mm (10.1in x 16.1in x 9.9in). Weight shall be 9.5kg (21lbs).

The loudspeaker shall be the Martin Audio CDD8.

Features

Ultra-Compact, CDD™ passive two-way system

Coaxial Differential Dispersion™ technology

User-rotatable coaxial drive unit

Screw-free perforated steel grille

Discreet mounting accessories

A
Elegan
Vertic
8Ω no
Black

T
F
D
R
S
M
N
D
C
E

FINISH
PROTECTIVE GRILLE
CONNECTORS
PIN CONNECTIONS
FITTINGS
DIMENSIONS
WEIGHT