

INPUTS	2 electronically balance	
MARTIN AUDIO M3+	20K ohms (10K ohms pe	
CMRR	60dB 20Hz - 10kHz	
Šifra: 10440	3 pin female XLR	
CONNECTIONS	4 electronically balanced	
Kategorija proizvoda: Pa Rack Ostalo		
Proizvođač: Martin Audio		
SOURCE IMPEDANCE	62 ohms	
MIN. LOAD IMPEDANCE	600 ohms	
MAX. OUTPUT	+20dBu into 600 ohms	
CONNECTIONS	3 pin male XLR	
FREQUENCY RESPONSE	-3dB @ 18Hz 12dB/octave -3dB @ 45KHz 12dB/octave (ultimately set by system parameters)	
DISTORTION + NOISE	0.01% THD @ 2V output (limiters cancelled)	
SIGNAL + NOISE/NOISE RATIO	> 100dB @ 2V output	
LIMITERS	Individual for each channel Ratio 20:1. Threshold range -12dBu to +12dBu in 16 steps	
MAINS SUPPLY	Captive 2m 3 core cable	
MAINS VOLTAGE	Internally selectable by hard wire link 100 - 120/220 - 240V. AC, 50/60Hz Voltage tolerance on each setting $\pm$ 10%	
MAINS FUSE	100 - 120V and 220 - 240V: 160mA Type 'T' (L)	
DIMENSIONS	(W) 482mm x (H) 44mm x (D) 155mm (W) 19ins x (H) 1.75ins (1U) x (D) 6.1ins	
WEIGHT	2.4fg (5.28lbs)	

**Cena: 114.360,00 rsd**

+  
 Technical Drawing - View  
[Martin Audio Blackline M3+ Tech Drawing](#)