

## MARTIN MAGNUM 2000 - Dim mašina B-Stock

Šifra: 6299  
Kategorija proizvoda: Dim Mašine  
Proizvođač: Martin

**Cena: 93.480,00 rsd**



Ovaj

uređaj visokog kvaliteta i performansi je korišten za opremanje enerijera kluba u Ashoka Hotelu u Nju Delhiju u Indiji, a više o tome možete pročitati na 98 stranici Mondo dr časopisa, ako kliknete na sliku ispod.

[gateway to india](#) page not found (type unknown)

### Magnum 2000TM

The most specified fog machine in the world. The Magnum 2000 is the authority in portable fog machines. Few other portable foggers can match the optional DMX controlled output of the Magnum 2000, or its logical plug and fog simplicity.

Solid reliability and quality of operation has made the Magnum 2000 the most specified fog machine in the world. Immense fog outputs create an instant billow of dense fog, perfect for generating immediate dance floor atmosphere and ideal for mid-air lighting effects.

Its advanced on-board technology, in conjunction with a specially designed heating element, give the Magnum 2000 a totally variable fog output and a heat up time of only 8 minutes.

With the large self contained fluid capacity of 9.5 liters, there's no need for mid-evening refills, and a plug-in remote control keeps you on the ground.

The Magnum 2000 is suited for clubs of all sizes and road show DJs. It comes complete with a truss mounting bracket for easy installation as well as carrying handles to suit all mobile and fixed installations

700 m<sup>3</sup>/min fog output

1600 W heat exchanger

8 min heat-up time

Floor standing or truss mounting

9.5 liter fluid capacity

Different fluid options for different applications

DMX with optional DMX interface module

On-board control panel

Removable panel for remote control

Timer and output level remote control

Magnum 2000TM Specifications

The most specified fog machine in the world. The Magnum 2000 is the authority in portable fog machines. Few other portable foggers can match the optional DMX controlled output of the Magnum 2000, or its logical plug and fog simplicity.

#### Features

700 m<sup>3</sup>/min fog output

1600 W heat exchanger  
8 min heat-up time  
Floor standing or truss mounting  
9.5 liter fluid capacity  
Different fluid options for different applications  
DMX with optional DMX interface module  
On-board control panel  
Removable panel for remote control  
Timer and output level remote control

Length: 695 mm (27.4 in.)  
Width: 356 mm (14.0 in.)  
Height: 325 mm (12.8 in.)  
Dry weight: 13 kg (28.7 lbs.)

Max. fog output (approx.): 700 m<sup>3</sup> per minute  
Max. operating time at full output (approx.): 180 minutes  
Warm-up time (approx.): 8 minutes

Control options: Remote control (supplied), DMX with optional DMX interface module  
Remote control features: Instant or timer-controlled variable output

Housing: Steel & aluminum  
Heat exchanger: 1500 W, direct thermal protection

Fluid pump: Oscillating piston, high pressure  
Onboard fluid capacity: 9.5 l  
Fluid consumption at peak output: 95 ml per minute

Orientation: Floor or flying kit

Remote control: 3-pin locking XLR  
0-10 V analog: 3-pin locking XLR  
Power cable entry: Hard-wired

AC power (EU models): 220-240 V nominal, 50 Hz  
AC power (US models): 110-120 V nominal, 60 Hz  
Main fuse (220-240 V power): 10 A  
Main fuse (110-120 V power): 15 A

Maximum ambient temperature (Ta max.): 40° C (104° F)  
Exterior surface temperature, steady state: 50° C (122° F)  
Max. nozzle temperature: 200° C (392° F)