

MARTIN RUSH Strobe 1 5x5

Šifra: 8985
Kategorija proizvoda: Strobovi
Proizvođač: Martin

Cena: 95.880,00 rsd



RUSH Strobe 1

This white strobe, model RUSH 1, is a 5x5 LED matrix panel with individually-controllable LEDs. Controllable via multiple DMX options or sound activated, it includes preprogrammed effect, letter and number macros for easy-to-produce graphics and messaging. Panels link via an integrated horizontal and vertical locking mechanism.

White LED strobe/blinder

Individually controllable LEDs
 Linkable - integrated horizontal and vertical locking

Controllable via multiple DMX options or sound activated, it includes preprogrammed macros for easy-to-produce graphics and messaging. link via an integrated horizontal and vertical locking mechanism. (effects, letters, numbers, etc.)

Features	
DMX or sound activated	
White LED strobe/blinder	5 x 5 matrix panel
Individually controllable LEDs	Preprogrammed macros (effects, letters, numbers, etc.)
Linkable - integrated horizontal and vertical locking	DMX or sound activated
Multiple DMX control options	3 & 5 pin XLR
Length: 500 mm (19.7 in.)	
Width: 101 mm (4.0 in.)	
Height: 500 mm (19.7 in.)	
Weight: 9.5 kg (20.9 lbs.)	
Strobe effect: Electronic, with regular and random pulse, burst and strobe effects	
Pre-programmed effects: Effect, letter and number display macros	
Electronic dimming: 0 - 100% continuous, individually dimmable pixels	
Effects orientation: Standard or inverted 180°	
Control options: DMX, stand-alone	
DMX channels: 4/25/29	
Stand-alone trigger options: Music trig, auto trig	
Stand-alone sequences: 8 pre-programmed shows or random show	
Stand-alone memory: 20 scenes	
Setting and addressing: Control panel with LCD display	
DMX compliance: USITT DMX512/1990	
Light source: 25 x 5 W Cree cool white LEDs	
Color temperature: 6000 - 6500 K	
Minimum LED lifetime: 50 000 hours (to >70% luminous output)*	
<i>*Manufacturer's figure obtained under manufacturer's test conditions</i>	

Multiple DMX control options

Color: Black

Housing: Steel

Protection rating: IP20

Location: Indoor use only, must be fastened to surface or structure

Mounting points: Integral hanging brackets (removable), side-by side mounting locks

Orientation: Any

AC power in/thru: Neutrik PowerCon

DMX data in/out: 3-pin and 5-pin locking XLR

AC power: 100-240 V nominal, 50/60 Hz

Typical total power consumption: 148 W

Power consumption figures are typical, not maximum. Allow for +/-10% variation.

Cooling: Forced air (temperature-regulated, low noise)

Maximum ambient temperature (Ta max.): 40° C (104° F)

Minimum ambient temperature (Ta min.): 0° C (32° F)

Mounting brackets incl. screws

Power cable 1.5 m (4.9 ft.)

RUSH Software Uploader 1™

Downloads

Image not found or type unknown



[RUSH Strobe 1 5x5 Specification](#)