

## MOTU 828x - Zvučna kartica

### MOTU 828x - Zvučna kartica

Šifra: 316

Kategorija proizvoda: USB Zvučne kartice

Proizvođač: MOTU

Cena: **89.880,00** rsd

#### How can one audio interface offer this much I/O?

We pack it in, like no one else can: two combo-style mic/guitar inputs with preamps, 8 balanced analog in/out, XLR main outs, 16 channels of ADAT optical (8 channels at 96 kHz), plus S/PDIF, word clock and MIDI. Connect all of your studio gear, including microphones, guitars, synths, keyboards, drum machines and even effects processors.

#### Technical Specifications

<b>Converters</b>	24-bit
<b>Sample rates</b>	44.1, 48, 88.2, 96, 176.4, 192 kHz
<b>Analog inputs</b>	2 x XLR/TRS combo-style mic/guitar inputs 8 x 1/4" TRS line inputs (balanced/unbalanced)
<b>Analog outputs</b>	2 x XLR balanced main out 8 x 1/4" balanced TRS line out 2 x 1/4" TRS stereo headphone
<b>Digital I/O</b>	16 channels of ADAT optical at 1x sample rates 8 channels of SMUX optical at 2x sample rates 2-channel TOSlink (optical S/PDIF) up to 96 kHz
<b>Total I/O</b>	2-channel RCA S/PDIF up to 96 kHz 28 inputs and 30 outputs at 1x sample rates 20 inputs and 22 outputs at 2x sample rates
<b>Computer I/O</b>	10 inputs and 10 outputs at 4x sample rates 1 x Thunderbolt (compatible with 1 and 2) 1 x USB 2.0 (compatible with 3.0)
<b>Sync I/O</b>	1 x SMPTE time code in (LTC) 1 x SMPTE time code out (LTC) 1 x word clock in
<b>Headphone output</b>	1 x word clock out 1 x 1/4" TRS stereo phone (assignable)
<b>Phantom power</b>	1 x 1/4" TRS stereo phone (mirrors main outs) 2 x individual +48V

2 x XLR/TRS combo mic/guitar in  
2 x 1/4" TRS phone  
2 x digital rotary encoders • phone/main volume  
2 x digital rotary encoders • mic trim  
4 x switches • Pad and 48V Phantom  
4 x digital rotary encoders for LCD control  
2 x 16 character LCD  
8 x 4-segment ladder LEDs • 1/4-inch analog in  
8 x activity LED • 1/4-inch analog out  
2 x 4-segment ladder LEDs • RCA S/PDIF in  
2 x activity LED • RCA S/PDIF out  
2 x 10-segment LEDs • mic in with V-Limit  
2 x 5-segment ladder LEDs • main outs  
International 100-240V autoswitching supply  
6 x LED • sample rate indicator  
50-60 Hz • 20 Watts  
1 x LED • LOCK/TACH indicator  
2 x activity LEDs • optical bank A/B  
1 x activity LED • MIDI in/out  
1 x AC power switch

**Power**

**Front panel**