

MOTU 828x - Zvučna kartica

MOTU 828x - Zvučna kartica

Šifra: 316
 Kategorija proizvoda: USB Zvučne kartice
 Proizvođač: MOTU

Cena: **115.080,00** rsd

How can one audio interface offer this much I/O?

We pack it in, like no one else can: two combo-style mic/guitar inputs with preamps, 8 balanced analog in/out, XLR main outs, 16 channels of ADAT optical (8 channels at 96 kHz), plus S/PDIF, word clock and MIDI. Connect all of your studio gear, including microphones, guitars, synths, keyboards, drum machines and even effects processors.

Technical Specifications

Converters	24-bit
Sample rates	44.1, 48, 88.2, 96, 176.4, 192 kHz
Analog inputs	2 x XLR/TRS combo-style mic/guitar inputs 8 x 1/4" TRS line inputs (balanced/unbalanced)
Analog outputs	2 x XLR balanced main out 8 x 1/4" balanced TRS line out 2 x 1/4" TRS stereo headphone
Digital I/O	16 channels of ADAT optical at 1x sample rates 8 channels of SMUX optical at 2x sample rates 2-channel TOSlink (optical S/PDIF) up to 96 kHz
Total I/O	2-channel RCA S/PDIF up to 96 kHz 28 inputs and 30 outputs at 1x sample rates 20 inputs and 22 outputs at 2x sample rates
Computer I/O	10 inputs and 10 outputs at 4x sample rates 1 x Thunderbolt (compatible with 1 and 2) 1 x USB 2.0 (compatible with 3.0)
Sync I/O	1 x SMPTE time code in (LTC) 1 x SMPTE time code out (LTC) 1 x word clock in
Headphone output	1 x word clock out 1 x 1/4" TRS stereo phone (assignable)
Phantom power	1 x 1/4" TRS stereo phone (mirrors main outs) 2 x individual +48V

2 x XLR/TRS combo mic/guitar in
 2 x 1/4" TRS phone
 2 x digital rotary encoders • phone/main volume
 2 x digital rotary encoders • mic trim
 4 x switches • Pad and 48V Phantom
 4 x digital rotary encoders for LCD control
 2 x 16 character LCD
 8 x 4-segment ladder LEDs • 1/4-inch analog in
 8 x activity LED • 1/4-inch analog out
 2 x 4-segment ladder LEDs • RCA S/PDIF in
 2 x activity LED • RCA S/PDIF out
 2 x 10-segment LEDs • mic in with V-Limit
 2 x 5-segment ladder LEDs • main outs
 International 100-240V, autoswitching supply
 6 x LED • sample rate indicator
 50-60 Hz • 20 Watts
 1 x LED • LOCK/TACH indicator
 2 x activity LEDs • optical bank A/B
 1 x activity LED • MIDI in/out
 1 x AC power switch

Power

Front panel