

MXL V67i - Studijski mikrofon - Studijski lampaški mikrofon

Šifra: 10401

Kategorija proizvoda: Sa Velikom Dijafragmom

Proizvođač: MXL

Cena: 20.280,00 rsd



Its
low-

frequency roll-off minimizes hum, proximity effect and other low-frequency noise. The V67i Tube is packaged with a power supply, cable, shockmount, and storage case.

12AT7 Dual Triode Vacuum Tube

The V67i Tube microphone reproduces signals with warmth and smooth high-end while maintaining the flexibility of selecting between "Warm" and "Bright" signal responses.

0 and -10 dB Attenuation

A -10 dB Pad switch maximizes headroom and minimizes distortion while capturing excessive transients (peaks).

Low-Frequency Roll-Off

Its low-frequency roll-off minimizes hum, proximity effect and other low-frequency noise.

MXL V67i Specs

Operating Principle Pressure Gradient

Capsule Condenser

Diaphragm 1.26" / 32.00 mm

Polar Pattern Cardioid

Circuitry Tube

Pad -10 dB

Low-Cut Filter @ 150 Hz

Frequency Range 30 Hz to 20 kHz

Maximum SPL 140 dB SPL

150 dB SPL

Impedance 200 Ohms

Sensitivity 22 mV/Pa

Signal-to-Noise Ratio 78 dB A-Weighted

Equivalent Noise Level 22 dB

Length 8.27" / 210 mm

Diameter 1.85" / 47 mm

Weight 1.5 lb / 680.38 g