

Neutrik NF2C B/2

Šifra: 8158

Kategorija proizvoda: Konektori

Proizvođač: Neutrik

Cena: **3.360,00** rsd

Pair of professional `Phono Plug` (`RCA` - or `CINCH` - type) - marked red and black.
Including 2 x 2 strain reliefs for cable O.D. 3.0 mm to 7.3 mm. Additional strain relief for cable O.D. up to 8.0 mm available as accessory.

Features & Benefits

Makes ground before signal contact and breaks signal before ground

No more disturbing noise and broken speaker cones

Precis

Neutrik unique chuck type strain relief

Gold

Sleek barrel with soft touch surface and coloured shrink sleeve

Impro

Title

NF2C-B/2

Connection Type

Profi

Gender

male

Electrical

Capacitance between contacts

≤ 7 pF

Contact resistance

>100G mΩ (inner)

Dielectric strength

1,5 kVdc

Insulation resistance

> 100 GΩ

Rated current per contact

16 A

Rated voltage

50 V

Mechanical

Cable O.D.

3.0 - 7.3 mm

Lifetime

> 2000 mating cycles

Wiresize

2,5 mm²

Wiresize

14 AWG

Wiring

Solder contacts

Material

Contact plating

5 µm Au over 5 µm Ni

Contacts

Brass (CuZn39Pb3)

Insert

PBTP 20 % GR

Shell

Brass (CuZn39Pb3)

Strain relief

Polyacetal (POM)

Environmental

Flammability

UL 94 HB

Standard compliance

IEC 601-14

Protection class

IP 40

Solderability

Complies with IEC 68-2-20

Temperature range

-30 °C to +80 °C

Downloads

Assembly Instruction - Profi

Image not found or type unknown

[Assembly Instruction - Profi](#)

Product Guide 2012, 03 Plugs+Jacks

Image not found or type unknown

[Product Guide 2012, 03 Plugs+Jacks](#)

Drawing NF2C

Image not found or type unknown

[Drawing NF2C](#)

Drawing NF2C

Image not found or type unknown

[Drawing NF2C](#)