

Neutrik NP2RX type Ugaoni 6.3mm mono jack

## Neutrik NP2RX - Ugaoni 6.3mm mono jack

Šifra: 6685  
 Kategorija proizvoda: Konektori  
 Proizvođač: Neutrik

Cena: **480,00** rsd

### Product

Connector Type Plug  
 Gender male

### Electrical

Contact resistance depends on mating connector mΩ  
 Dielectric strength 1 kVdc  
 Insulation resistance > 2 GΩ (initial)  
 Insulation resistance ≥ 1 GΩ (after damp heat test)  
 Rated current per contact ≤ 15 A

### Mechanical

Cable O.D. 4 - 7 mm  
 Wire size 1 mm<sup>2</sup>  
 Wire size 18 AWG  
 Wiring Solder contacts  
 RW / Straight yes

### Material

Bushing Polyacetal (POM) + PU  
 Contact plating 2 μm Ni (Su)  
 Contacts Brass (CuZn39Pb3)  
 Insert Polyamide (PA 6.6 30 % GR)  
 Shell Zinc diecast (ZnAl4Cu1)  
 Shell plating Nickel  
 Strain relief Polyacetal (POM)

### Environmental

Standard compliance IEC 60603-11 / EIA RS-453  
 Solderability Complies with IEC 68-2-20  
 Temperature range -20 °C to +65 °C