

Neutrik NP2RX - Ugaoni 6.3mm mono jack

## Neutrik NP2RX - Ugaoni 6.3mm mono jack

Šifra: 6685

Kategorija proizvoda: Konektori

Proizvođač: Neutrik

Cena: **480,00** rsd

### Product

Connector Type

Plug

Gender

male

### Electrical

Contact resistance

depends on mating connector mΩ

Dielectric strength

1 kVdc

Insulation resistance

> 2 GΩ (initial)

Insulation resistance

≥ 1 GΩ (after damp heat test)

Rated current per contact

≤ 15 A

### Mechanical

Cable O.D.

4 - 7 mm

Wire size

1 mm<sup>2</sup>

Wire size

18 AWG

Wiring

Solder contacts

RW / Straight

yes

### Material

Bushing

Polyacetal (POM) + PU

Contact plating

2 μm Ni (Su)

Contacts

Brass (CuZn39Pb3)

Insert

Polyamide (PA 6.6 30 % GR)

Shell

Zinc diecast (ZnAl4Cu1)

Shell plating

Nickel

Strain relief

Polyacetal (POM)

### Environmental

Standard compliance

IEC 60603-11 / EIA RS-453

Solderability

Complies with IEC 68-2-20

Temperature range

-20 °C to +65 °C