

Neutrik NP3X or type unknown

## Neutrik NP3X

Šifra: 1631  
Kategorija proizvoda: Konektori  
Proizvođač: NeutrikCena: **600,00** rsd

### Product

Connector Type  
GenderPlug  
male

### Electrical

Contact resistance  
Dielectric strength  
Insulation resistance  
Insulation resistance  
Rated current per contactdepends on mating connector mΩ  
1 kVdc  
> 2 GΩ (initial)  
≥ 1 GΩ (after damp heat test)  
≤ 15 A

### Mechanical

Cable O.D.  
Wire size  
Wire size  
Wiring4 - 7 mm  
1 mm<sup>2</sup>  
18 AWG  
Solder contacts

### Material

Bushing  
Contact plating  
Contacts  
Insert  
Shell  
Shell plating  
Strain reliefPolyacetal (POM) + PU  
2 μm Ni (Su)  
Brass (CuZn39Pb3)  
Polyamide (PA 6.6 30 % GR)  
Zinc diecast (ZnAl4Cu1)  
Nickel  
Polyacetal (POM)

### Environmental

Standard compliance  
Solderability  
Temperature rangeIEC 60603-11 / EIA RS-453  
Complies with IEC 68-2-20  
-20 °C to +65 °C