

Eighteensound 6ND430 8 ohm - Zvučnik

Eighteensound 6ND430 8 ohm - Zvučnik

Šifra: 6861
Kategorija proizvoda: 6 i manje
Proizvođač: Eighteensound

Cena: **23.880,00** rsd

6ND430 LF Neodymium Driver

Key features

92,5 dB SPL 1W / 1m average sensitivity

45 mm (1,77 in) aluminum voice coil

200 W

Neodymium motor assembly

Weather

Improved heat dissipation via unique basket design

Ideal

Downloads

 [Data sheet](#) found or type unknown

 [Drawing](#) found or type unknown

 [022066N430-6ND430-16.pdf](#)

 [6ND430](#) found or type unknown

Description

The 6ND430 is a 6 inch neodymium woofer designed for low frequency reproduction in 2-way systems or multiway systems where both low weight and high intelligibility are required.

The speaker has been specifically designed for compact reflex enclosures where high quality low-bass and mid frequencies are required such as studio monitoring applications. It is also currently used in line array or multiway systems with excellent results.

The extremely powerful external neodymium magnet assembly assures high flux concentration, low power compression and excellent heat exchange. The levels of force factor and power handling are, as a consequence, at a top professional level with an optimum power to weight ratio.

A consistent heat transfer is guaranteed by the encapsulation of the magnetic structure in the interior of the basket, offering a large contact space between the back plate and the dissipating structure.

Particular effort was given to the surround shape and material design in order to minimise the resonances on mid range frequencies. The new design, realised with specified rubber based material density, offers a consistent dampening to typical bell modes.

The 45 mm voice coil is made from a light-weight aluminum wire and assures linearity and high power handling.

A proprietary humidity-block cone treatment makes the transducer suitable for outdoor use in adverse weather conditions. In addition, a special coating applied to both the top and back plates makes the 6ND430 far more resistant to the corrosive effects of salts and oxidization.

GENERAL SPECIFICATIONS

Nominal Diameter	152mm (6 in)
Rated Impedance	8 Ohm
AES Power	200 W

Program Power (1)	260 W
Peak Power (2)	500 W
Sensitivity (3)	92,5 dB
Frequency Range (4)	63 ÷ 5500 Hz
Power Compression @-10dB (5)	1,0 dB
Power Compression @-3dB	1,5 dB
Power Compression @Full Power	2,9 dB
Max Recomm. Frequency	3000 Hz
Recomm. Enclosure Volume	10 ÷ 40 lt. (0,35 ÷ 1,41 cuft)
Minimum Impedance	6,1 Ohm at 25°C
Max Peak To Peak Excursion	22 mm (0,87 in)
Voice Coil Diameter	44 mm (1,75 in)
Voice Coil Winding Material	aluminum
Suspension	Single roll, Rubber
Cone	Curvilinear, Paper

THIELE SMALL PARAMETERS (6)

Fs	61 Hz
Re	5.5 Ohm
Sd	0,0133 sq.mt. (20,6 sq.in.)
Qms	6.5
Qes	0.28
Qts	0.27
Vas	12.6 lt. (0,4 cuft)
Mms	13,3 gr. (0,03 lb)
BL	10.0 Tm
Linear Mathematical Xmax (7)	± 5 mm (±0,20 in)
Le (1kHz)	0.28 mH
Ref. Efficiency 1W@1m (half space)	92 dB

MOUNTING INFORMATION

Overall diameter	162 mm (6,38 in)
N. of mounting holes	4
Mounting holes diameter	5,5 mm (0,22 in)
Bolt circle diameter	170 mm (6,69 in)
Front mount baffle cutout ø	148 mm (5,38 in)
Rear mount baffle cutout ø	148 mm (5,38 in)
Total depth	73 mm (2,87 in)
Flange and gasket thickness	9,5 mm (0,37 in)
Net weight	1,25 kg (2,76 lb)
Shipping weight	1,8 kg (3,97 lb)
CardBoard Packaging dimensions	170 x 170 x 80 mm (6,69 x 6,69 x 3,15 in)

FREQUENCY RESPONSE CURVE OF 6ND430 MADE ON 18 LIT. ENCLOSURE TUNED AT 60HZ IN FREE FIELD (4PI) ENVIRONMENT. ENCLOSURE CLOSES THE REAR OF THE DRIVER. THE THIN LINE REPRESENTS 45 DEG. OFF AXIS FREQUENCY RESPONSE

FREQUENCY RESPONSE CURVE OF 6ND430 MADE ON 18 LIT. ENCLOSURE TUNED AT 60HZ IN FREE FIELD (4PI)

Image not found or type unknown

FREE AIR IMPEDANCE MAGNITUDE CURVE

FREE AIR IMPEDANCE MAGNITUDE CURVE

Image not found or type unknown