

logo not found or type unknown

Firma: Player Plus doo  
Adresa: Svetogorska 9  
Telefon: +381 11 3347 442  
Fax: +381 11 3347 615  
PIB: 106966344  
E-mail: porudzbine@player.rs

## Eighteensound HD1050 8 Ohm - Visokotonac

---

Šifra: 7027  
Kategorija proizvoda: HF Driveri (Visokotonci)  
Proizvođač: Eighteensound

**Cena: 11.880,00 rsd**

Eighteensound HD1050 8 Ohm - Visokotonac

HD1050    HF Compression Driver

Key features

- 107 dB SPL 1W / 1m average sensitivity


44 mm (1 3/4 inch) voice coil diameter


Titanium dome over PEN suspension
- 1 inch exit throat

100 Watt program power handling

Proprietary phase plug design

Downloads

[Data sheet](#)

[Drawing](#)

Description

The HD1050 one inch exit high frequency compression driver has been designed for use in high quality audio systems.

Equipped with Eighteen Sound proprietary Phase Plug architecture, the HD1050 has been designed to give high level manufacturing consistency and smooth coherent wave front at the horn entrance across the whole working frequency range. The phase plug with its short openings and high flare rate value assures low distortion and demonstrates remarkable improvements in mid-high frequency reproduction.

The diaphragm assembly is composed of a titanium dome sandwiched to a proprietary treated polyester suspension unit. It has been designed to maintain low resonance, lowering the minimum crossover point value at 1,6kHz. An edge-wound aluminum voice coil, wound on proprietary treated Nomex, completes the diaphragm assembly. Thanks to its physical properties, the proprietary treated Nomex former has a 30% higher value of tensile elongation at a working operative temperature (200°C) when compared to Kapton. This feature enables proper energy transfer control from the voice coil to the dome in real working conditions. Moreover, this proprietary former material is also suitable to for use in higher moisture content environments.

The HD1050 powerful ceramic magnet assembly has been designed to obtain 16 KGauss in the gap and within a compact ferrite motor structure.

GENERAL SPECIFICATIONS	
Throat Diameter	25,4 mm (1 in)
Rated Impedance	8 ohm
DC Resistance	5,3 Ohm
Minimum Impedance	7 Ohm at 4000Hz
AES power (1)	50 W above 1,6 kHz
Program power (2)	100 W above 1,6 kHz
Sensitivity(1W@1m) (3)	107 dB
Frequency Range	1600Hz ÷ 20kHz
Recomm. Xover Frequency	1600Hz (12dB/oct slope)
Diaphragm Material	Titanium - PEN
Voice Coil Diameter	44,4 mm (1 3/4 in)
Voice Coil Winding Material	Edge-wound aluminum
Magnet Material	Ferrite
Flux Density	1,6 T

BL Factor	7,4 N/A
Polarity	Positive voltage on + terminal gives positive pressure in the throat

**MOUNTING INFORMATION**

Overall diameter	110 mm (4,3 in)
Mounting holes diameter	4 M6 holes 90° at Ø 76 mm (3 in)
Bolt circle diameter	76 mm (3 in)
Total depth	60,5 mm (2,38 in)
Net weight	1,8 Kg (4 lb)
Shipping weight	1,9 Kg (4,22 lb)
CardBoard Packaging dimensions	110x110x63 mm (4,3x4,3x2,5 in)

**HD1050 MEASURED WITH 1W INPUT ON RATED IMPEDANCE AT 1M DISTANCE ON XT1086 HORN MOUTH AXIS**

HD1050 MEASURED WITH 1W INPUT ON RATED IMPEDANCE AT 1M DISTANCE ON XT1086 HORN MOUTH AXIS

**FREE AIR IMPEDANCE MAGNITUDE CURVE**

FREE AIR IMPEDANCE MAGNITUDE CURVE