

Power specifications

LEM Proton 2200 plus - Razglasno pojačalo

Šifra: 2031

Kategorija proizvoda: Razglasna Pojačala

Proizvođač: LEM

8 ohms: 1.650W + 650W
 4 ohms: 1.100W + 1.100W
 8 ohms bridged: 2.200W

Cena: 71.880,00 rsd



(1 kHz, THD 1%) Both channels

Electrical specifications

Input sensitivity 0dB (0.775V)

Input impedance 10 kohms (balanced)

Frequency response 10Hz - 50kHz (-0,5dB)

Voltage gain 39 dB

Slew rate 22 V/ms

Damping factor Higher then 400:1 @ 1kHz, 8 ohms

Crosstalk -82dB (1kHz)

S/N ratio -98dB

Harmonic distorsion (THD) Lower then 0,1% (ref 20Hz -20kHz)

Intermodulation distortion SMPTE Lower then 0,1% (SMPTE method, 60Hz & 7kHz, 400:1 ratio)

General specifications

Protections Power transformer thermal protection; short circuit protection; sensor for current on outputs; clip limiter on each channel; soft-start circuit (1000P to 2200P)

Controls On/off switch, 21-detect input level control for each channel, Mode selector, Shield selector

Indicators Power On: 1 red LED
 Bridge: 1 red LED
 Protect: 1 red LED
 Level: 2 x 5 LED meter
 Limit: 1 red LED

Connections Input: 1 XLR-F + 1 1/4' jack in parallel for each channel
 Output: 2 binding post + 1 speakon for each channel (400-1500); 1 speakon for each channel + 1 speakon for Bridge output (1800-2200)

Power supply	See label on the apparatus
Dimensions (W x H x D)	483 x 88 x 456 mm / 19' x 3,46' x 17,95'
Weight	25 kg / 55,1 lbs

