

Firma: Player Plus doo Adresa: Svetogorska 9 Telefon: +381 11 3347 442 Fax: +381 11 3347 615

PIB: 106966344

E-mail: porudzbine@player.rs

REGOOP follows for type unknown

RELOOP PLAY

Šifra: 7710

Kategorija prozivoda: DVS Scratch Sistemi

Proizvođač: Reloop

Cena: 4.680,00 rsd

Play

USB-DJ-audio interface with 24-Bit sound quality

Most compact format

USB soui

Exte

With one of the many specific club signant

Elaborate connecting possibilities

Thanks to the elaborate connecting possibilities, Reloop Play offers two play modes. On the one hand there is the external mixer mode: with it, it is possible routing two separate stereo channels to an external mixer – this mode will be appreciated by all professional Traktor users. The second mode is called the controller mode: In this case a master outut is routed to the sound system and it is possible to connect headphones directly to the interface – this mode is especially appropriate for laptop DJs without further hardware. Both stero channels' volume can be comfortably adjusted via separate controllers. The signal status LEDs allow a visual monitoring so that everything remains in view and under control. Small, professional and always present: Plug&Play.

Technical Data

Minimum system requirements PC:

Windows XP (SP3), Win7 (32 bit/64 bit)

at least Pentium III / Intel Core Duo, 1 GHz Near 12008 recommended!)

Minimum system requirements Mac:

OS X 10.5/10.6

Intel Core Duo family

Dimensions: 80 x 20 x

65 mm

Weight: 85 g

Incl. ASIO driver CD, USB

cord

Features

Ultra portable 4-channel DI audio interface with 24 bit resolution Hi-speed USB 2.0 with low latency ASIO/CORE Audio drivers Hi-gain outputs for powerful club sound 2 stereo RCA outputs for use with an external DJ mixer Stereo 1/4" headphones output for use with software mixer 2 play modes: External mixer mode (2 separate channels can be routed to an external mixer). controller mode (1x master out is routed to the sound system and headphones can be connected directly to the interface) Volume controls and signal status LEDs for direct, visual monitoring Separate volume controllers for channels 1 & 2, master & headphones respectively USB bus powered Burglar-proof: Kensington lock Low latency ASIO/Core Audio drivers Compatible with Mac OS X and Windows XP/Vista/7