

MARTIN RUSH Wizard - Skener

MARTIN RUSH Wizard - Skener

Šifra: 10263
Kategorija proizvoda: Skeneri
Proizvođač: Martin

Cena: 137.880,00 rsd

Tech Specs

PhysicalLength:447 mm (17.6 in.)
Width:500 mm (19.7 in.)
Height:195 mm (7.7 in.)
Weight:9.3 kg (20.5 lbs.) including bracket
Dynamic EffectsMotorized rotating parabolic mirror dish
Motorized mirror drum:180° pan (swivel) and 360°

tilt (continuous rotation)

Color / animation wheel:7 colors plus 2 x open, twinkle animation effect

Gobo wheel:13 gobos + open, wheel scrolling and continuous rotation, shake effect

Shutter:0 - 100% continuous dimming, variable & random strobe & pulse effects, instant open & blackout

Pre-programmed effects:Full range of macro effects

Control and ProgrammingControl options:DMX, stand-alone, master/slave

DMX channels:10

Stand-alone trigger options:Music trig, auto trig

Music trig also settable via DMX

Setting and addressing:Control panel with backlit LCD display

Protocol:USITT DMX512/1990

Firmware update:Serial upload via DMX link

LampType:130 W short-arc discharge with reflector

Color temperature:8800 K

Average lifetime:6000 hours*

*Manufacturer's figure

OpticsManual focus:2 m - 20 m (6 ft. 7 in. - 65 ft. 8 in.)

ConstructionHousing:High-impact flame-retardant thermoplastic

Color(s):Black

Protection rating:IP20

InstallationMounting points:Adjustable bracket

Orientation:Any

Location:Indoor use only, must be fastened to surface or structure

Minimum distance to illuminated surfaces:0.5 m (19.7 in.)

Minimum distance to combustible materials:0.3 m (11.9 in.)

Minimum clearance around fan and air vents:0.3 m (11.9 in.)

ConnectionsAC power in/thru:Neutrik PowerCon

DMX data in/out:5-pin locking XLR

ElectricalAC power:100-240 V nominal, 50/60 Hz

Typical total power consumption:200 W

Power consumption figures are typical, not maximum. Allow for +/-10% variation.

Typical Power and Current110 V, 60 Hz:1.9 A, 200 W, PF 0.99

230 V, 50 Hz:0.9 A, 196 W, PF 0.95

Measurements made at nominal voltage with all LEDs at full intensity. Allow for a deviation of +/- 10%.

ThermalCooling:Forced air (temperature-regulated, low noise)

Maximum ambient temperature (Ta max.):40° C (104° F)

Minimum ambient temperature:0° C (32° F)

Total heat dissipation (calculated, +/- 10%):685 BTU/hr.

ApprovalsEU safety:EN 60598-2-17 (EN 60598-1), EN 62471, EN 62493

EU EMC:EN 55015, EN 55103-1, EN 55103-2, EN 61000-3-2, EN 61000-3-3, EN 61547

US safety:UL 1573

US EMC:FCC Part 15 Class A

Canadian safety:CSA C22.2 No. 166

Canadian EMC:ICES-003 Class A

Australia/NZ:C-TICK N4241

Image not found. Image type unknown



Included ItemsLamp (installed)

Mounting bracket

Power cable, 1.5 m, without mains plug

AccessoriesCables, 16 A, for connection to power in chains

Power input cable, 14 AWG, SJT, 1.5 mm², H05VV-F, with PowerCon input connector, 3 m (9 ft. 11 in.):P/N 11541508

Power relay cable, 14 AWG, SJT, 1.5 mm², H05VV-F, with PowerCon input connector, 1.4 m (4 ft. 8 in.):P/N 11541509

Power relay cable, 14 AWG, SJT, 1.5 mm², H05VV-F, with PowerCon input connector, 2.25 m (7 ft. 5 in.):P/N 11541510

Power relay cable, 14 AWG, SJT, 1.5 mm², H05VV-F, with PowerCon input connector, 3.25 m (10 ft. 8 in.):P/N 11541511

Power connectors

Neutrik PowerCon NAC3FCA power input connector, cable mount, blue:P/N 05342804

Neutrik PowerCon NAC3FCB power output connector, cable mount, light grey:P/N 05342805

Installation hardware

G-clamp:P/N 91602003

Half-coupler clamp:P/N 91602005

DMX termination plug, 3-pin male XLR:P/N 91613017

5-pin male XLR to 3-pin female XLR adaptor:P/N 11820005

Safety cable, safe working load 50 kg (110.3 lbs.):P/N 91604003

Related ItemsRUSH Software Uploader 1™:P/N 91611399

Ordering InformationRUSH Wizard™ in cardboard box:P/N 90480070